

Nimbus apšvietimo prekių kainoraštis



Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
002-383	833.66.003	Q/R/CUBIC 36/49/64 SERIES, mounting ring direct mounting steel, galvanised	15.73	14.16
002-877	833.66.004	Q/CUBIC 9, mounting ring direct mounting steel, galvanised	7.20	6.48
003-727	833.66.005	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 12.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	686.07	617.46
003-756	833.66.006	ZEN IN S, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 55 lm, 1.5 W, 24 V DC, 3000 K, IP 20	168.19	151.37
003-757	833.66.007	ZEN IN S, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 55 lm, 1.5 W, 24 V DC, 3000 K, IP 20	168.19	151.37
003-758	833.66.008	ZEN IN M LONG POWER, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 340 lm, 6,0 W, 24 V DC, 3000 K, IP 20	290.40	261.36
003-759	833.66.009	ZEN IN M LONG POWER, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 6,0 W, 24 V DC, 3000 K, IP 20	290.40	261.36
003-761	833.66.010	MIKE INDIA 70 ACCENT, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 140 lm, 3,0 W, 24 V DC, 3000 K, IP 20	198.44	178.60
003-762	833.66.011	MIKE INDIA 70 ACCENT, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 140 lm, 3,0 W, 24 V DC, 3000 K, IP 20	198.44	178.60
003-763	833.66.012	MIKE INDIA 70 ACCENT LONG, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 280 lm, 6,0 W, 24 V DC, 3000 K, IP 20	257.73	231.96

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
003-764	833.66.013	MIKE INDIA 70 ACCENT LONG, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 280 lm, 6,0 W, 24 V DC, 3000 K, IP 20	257.73	231.96
003-780	833.66.014	MIKE INDIA 70 ACCENT, installation kit for flushmounted install. kit without space for converter steel	41.14	37.03
003-781	833.66.015	MIKE INDIA 70 ACCENT, installation kit for flushmounted install. kit with space for converter steel	59.29	53.36
003-782	833.66.016	MIKE INDIA 70 ACCENT LONG, installation kit for flushmounted install. kit without space for converter steel	48.40	43.56
003-783	833.66.017	MIKE INDIA 70 ACCENT LONG, installation kit for flushmounted install. kit with space for converter steel	65.34	58.81
003-907	833.66.018	PWM DIMMING UNIT dimnable, 1-10 V 24 V DC, output 24 V DC, 120 W, IP 20	217.80	196.02
004-018	833.66.020	ZEN IN M, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 85 lm, 1.5 W, 24 V DC, 3000 K, IP 20	202.07	181.86
004-019	833.66.021	ZEN IN M LONG, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 170 lm, 3.0 W, 24 V DC, 3000 K, IP 20	251.68	226.51
004-020	833.66.022	ZEN IN M, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 85 lm, 1.5 W, 24 V DC, 3000 K, IP 20	202.07	181.86
004-021	833.66.023	ZEN IN M LONG, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 170 lm, 3.0 W, 24 V DC, 3000 K, IP 20	251.68	226.51
004-022	833.66.024	ZEN ON, wall luminaire, near-ground with wall mounting set version for 24 V DC aluminium, anodised CRI 80 85 lm, 1.5 W, 24 V DC, 3000 K, IP 20	217.80	196.02
004-023	833.66.025	ZEN ON LONG, wall luminaire, near-ground with wall mounting set version for 24 V DC aluminium, anodised CRI 80 170 lm, 3.0 W, 24 V DC, 3000 K, IP 20	251.68	226.51

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
004-024	833.66.026	MIKE INDIA 50 ACCENT, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 55 lm, 1,5 W, 24 V DC, 3000 K, IP 20	170.61	153.55
004-025	833.66.027	MIKE INDIA 50 ACCENT LONG, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 110 lm, 3,0 W, 24 V DC, 3000 K, IP 20	198.44	178.60
004-026	833.66.028	MIKE INDIA 50 ACCENT, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 55 lm, 1,5 W, 24 V DC, 3000 K, IP 20	170.61	153.55
004-027	833.66.029	MIKE INDIA 50 ACCENT LONG, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 110 lm, 3,0 W, 24 V DC, 3000 K, IP 20	198.44	178.60
004-155	833.66.038	MODUL Q 36, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6.8 W, 24 V DC, 3000 K, IP 20	257.73	231.96
004-178	833.66.040	MODUL Q 9, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.7 W, 24 V DC, 3000 K, IP 20	143.99	129.59
004-180	833.66.041	MODUL Q 64, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1350 lm, 10.9 W, 24 V DC, 3000 K, IP 20	504.57	454.11
004-185	833.66.042	MODUL Q 36 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6.8 W, 24 V DC, 3000 K, IP 44	353.32	317.99

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
004-189	833.66.043	MODUL Q 36, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	273.46	246.11
004-191	833.66.044	MODUL Q 64, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 20	523.93	471.54
004-258	833.66.047	MODUL Q 64 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 44	560.23	504.21
004-542	833.66.048	ZEN IN M, installation kit for flushmounted install. kit with space for converter	65.34	58.81
004-543	833.66.049	ZEN IN M, installation kit for flushmounted install. kit without space for converter	50.82	45.74
004-544	833.66.050	ZEN IN M LONG, installation kit for flushmounted install. kit with space for converter	79.86	71.87
004-545	833.66.051	ZEN IN M LONG, installation kit for flushmounted install. kit without space for converter	60.50	54.45
004-546	833.66.052	MIKE INDIA 50 ACCENT, installation kit for flushmounted install. kit with space for converter steel	59.29	53.36
004-547	833.66.053	MIKE INDIA 50 ACCENT, installation kit for flushmounted install. kit without space for converter steel	44.77	40.29
004-548	833.66.054	MIKE INDIA 50 ACCENT LONG, installation kit for flushmounted install. kit with space for converter steel	61.71	55.54
004-549	833.66.055	MIKE INDIA 50 ACCENT LONG, installation kit for flushmounted install. kit without space for converter steel	41.14	37.03
004-785	833.66.058	MODUL Q 9 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,7 W, 24 V DC, 3000 K, IP 44	179.08	161.17

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
004-790	833.66.061	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring stainless steel, brushed CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	263.78	237.40
004-801	833.66.062	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, white, brilliant, powder-coated CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	239.58	215.62
004-803	833.66.063	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, silver, varnished CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	239.58	215.62
004-870	833.66.064	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with cavity bracket white, powder-coated CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	398.09	358.28
004-873	833.66.065	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring stainless steel, brushed CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 20	542.08	487.87
004-875	833.66.066	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, silver, varnished CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 20	523.93	471.54
004-876	833.66.067	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, white, brilliant, powder-coated CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 20	523.93	471.54
004-886	833.66.068	MODUL Q 144, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 24,4 W, 24 V DC, 3000 K, IP 20	892.98	803.68

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
005-225	833.66.069	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with cavity bracket silver, varnished CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	398.09	358.28
005-226	833.66.070	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	398.09	358.28
005-227	833.66.071	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring silver, varnished CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	398.09	358.28
005-365	833.66.072	MODUL Q 36 IN, concrete mounting box	130.68	117.61
005-366	833.66.073	Concrete mounting box	146.41	131.77
005-442	833.66.074	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 28,3 W, 230 V AC, 50 Hz, 3000 K, IP 20	1197.90	1078.11
005-443	833.66.075	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment version for 24 V DC acrylic, satin-frosted CRI 90 3.000 lm, 24,4 W, 24 V DC, 3000 K, IP 20	951.06	855.95
005-471	833.66.076	MODUL Q 144, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 24,4 W, 24 V DC, 3000 K, IP 20	925.65	833.09
005-551	833.66.077	CONVERTER switchable 230 V AC, 50 Hz, output 24 V DC, 20 W, IP 20 NP	83.49	75.14
005-563	833.66.078	CONVERTER switchable 230 V AC, 50 Hz, output 24 V DC, 75 W	269.83	242.85
005-678	833.66.079	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment dimmable, 1-10 V, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 28,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	1351.57	1216.41

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
005-679	833.66.080	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 28,9 W, 230 V AC, 50 Hz, 3000 K, IP 20	1410.86	1269.77
005-689	833.66.081	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, silver, varnished CRI 90 750 lm, 6.8 W, 24 V DC, 3000 K, IP 20	515.46	463.91
005-690	833.66.082	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, white, varnished CRI 90 750 lm, 6.8 W, 24 V DC, 3000 K, IP 20	515.46	463.91
005-693	833.66.083	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, silver, varnished CRI 90 750 lm, 8.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	649.77	584.79
005-694	833.66.084	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 8.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	649.77	584.79
005-751	833.66.085	L 120, suspended luminaire suspended mounting switchable max. suspended length 1800 mm with suspension kit, with canopy incl. converter aluminium, chrome plated CRI 80 1 826 lm, 32.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	1513.71	1362.34
005-752	833.66.086	L 120, suspended luminaire cavity mounting version for 24 V DC max. suspended length 1800 mm with suspension kit aluminium, chrome plated CRI 80 1 826 lm, 26.0 W, 24 V DC, 3000 K, IP 20	1216.05	1094.45
005-753	833.66.087	L 120, suspended luminaire suspended mounting switchable max. suspended length 1800 mm with suspension kit, with canopy incl. converter aluminium, anodised CRI 80 1 826 lm, 32.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	1322.53	1190.28

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
005-754	833.66.088	L 120, suspended luminaire cavity mounting version for 24 V DC max. suspended length 1800 mm with suspension kit aluminium, anodised CRI 80 1.826 lm, 26.0 W, 24 V DC, 3000 K, IP 20	1023.66	921.29
005-797	833.66.093	MODUL L, cover cavity mounting aluminium, white, matt, powder-coated	45.98	41.38
005-890	833.66.094	PWM DIMMING UNIT dimnable, 1-10 V 24 V DC, output 24 V DC, 120 W, IP 20	85.91	77.32
005-906	833.66.095	MODUL R 144, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 24.4 W, 24 V DC, 3000 K, IP 20	925.65	833.09
006-143	833.66.096	MODUL Q 49, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9.8 W, 24 V DC, 3000 K, IP 20	342.43	308.19
006-339	833.66.097	MODUL Q 100, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18.1 W, 24 V DC, 3000 K, IP 20	652.19	586.97
006-350	833.66.098	MODUL Q 49, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9.8 W, 24 V DC, 3000 K, IP 20	360.58	324.52
006-351	833.66.099	MODUL Q 49 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9.8 W, 24 V DC, 3000 K, IP 44	385.99	347.39
006-352	833.66.100	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	479.16	431.24

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
006-361	833.66.101	MODUL R 36, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	257.73	231.96
006-362	833.66.102	MODUL R 49, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1 050 lm, 9,8 W, 24 V DC, 3000 K, IP 20	378.73	340.86
006-363	833.66.103	MODUL R 64, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1 350 lm, 10,9 W, 24 V DC, 3000 K, IP 20	539.66	485.69
006-378	833.66.105	MODUL R 9, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,7 W, 24 V DC, 3000 K, IP 20	143.99	129.59
006-384	833.66.106	MODUL R 100, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2 150 lm, 18,1 W, 24 V DC, 3000 K, IP 20	665.50	598.95
006-415	833.66.107	MODUL R 9, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,7 W, 24 V DC, 3000 K, IP 20	171.82	154.64
006-418	833.66.108	MODUL R 36, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	273.46	246.11
006-419	833.66.109	MODUL R 36, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 750 lm, 8,3 W, 230 V AC, 50 Hz, 3000 K, IP 20	436.81	393.13

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
006-421	833.66.110	MODUL R 49, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9,8 W, 24 V DC, 3000 K, IP 20	392.04	352.84
006-422	833.66.111	MODUL R 49, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11,8 W, 230 V AC, 50 Hz, 3000 K, IP 20	515.46	463.91
006-424	833.66.112	MODUL R 64, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 20	559.02	503.12
006-425	833.66.113	MODUL R 64, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 12,9 W, 230 V AC, 50 Hz, 3000 K, IP 20	719.95	647.96
006-426	833.66.114	MODUL R 100, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18,1 W, 24 V DC, 3000 K, IP 20	701.80	631.62
006-428	833.66.115	MODUL R 100, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 21,5 W, 230 V AC, 50 Hz, 3000 K, IP 20	785.29	706.76
006-430	833.66.116	MODUL R 144, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 24,4 W, 24 V DC, 3000 K, IP 20	960.74	864.67
006-431	833.66.117	MODUL R 144, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 28,3 W, 230 V AC, 50 Hz, 3000 K, IP 20	1213.63	1092.27

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
006-436	833.66.118	MODUL Q 100, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18,1 W, 24 V DC, 3000 K, IP 20	684.86	616.37
006-437	833.66.119	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 21.5 W, 230 V AC, 50 Hz, 3000 K, IP 20	753.83	678.45
006-438	833.66.120	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment version for 24 V DC acrylic, satin-frosted CRI 90 2.150 lm, 18.1 W, 24 V DC, 3000 K, IP 20	701.80	631.62
006-442	833.66.121	MODUL R 9 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.7 W, 24 V DC, 3000 K, IP 44	189.97	170.97
006-443	833.66.122	MODUL R 36 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6.8 W, 24 V DC, 3000 K, IP 44	353.32	317.99
006-444	833.66.123	MODUL R 49 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9.8 W, 24 V DC, 3000 K, IP 44	423.50	381.15
006-445	833.66.124	MODUL R 64 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10.9 W, 24 V DC, 3000 K, IP 44	577.17	519.45
006-610	833.66.126	Q/R/CUBIC 36/49/64 SERIES, mounting ring cavity mounting / HaloX-O, mounting depth in cavity 40 mm steel, galvanised	33.88	30.49
006-645	833.66.127	L 120, suspended luminaire suspended mounting dimnable, 1-10 V max. suspended length 1800 mm with suspension kit, with canopy incl. converter aluminium, chrome plated CRI 80 1.826 lm, 32.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	1586.31	1427.68

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
006-646	833.66.128	L 120, suspended luminaire suspended mounting dimmable, 1-10 V max. suspended length 1800 mm with suspension kit, with canopy incl. converter aluminium, anodised CRI 80 1 826.1m 32.0 W 230 V AC 50 Hz 3000 K IP 20	1395.13	1255.62
006-668	833.66.129	L 120, converter set cavity mounting switchable 50 Hz, IP 20	73.81	66.43
006-991	833.66.130	MODUL R 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	398.09	358.28
007-391	833.66.131	MODUL R 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	398.09	358.28
007-393	833.66.132	MODUL R 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 20	515.46	463.91
007-395	833.66.133	MODUL R 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 8.3 W, 230 V AC 50 Hz 3000 K IP 20	649.77	584.79
007-407	833.66.134	MODUL R 9 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,7 W, 24 V DC, 3000 K, IP 44	217.80	196.02
007-409	833.66.135	MODUL R 36 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 44	369.05	332.15

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
007-418	833.66.136	MODUL R 49 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9,8 W, 24 V DC, 3000 K, IP 44	438.02	394.22
007-439	833.66.137	MODUL R 64 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 44	595.32	535.79
007-453	833.66.138	MODUL Q 49 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9,8 W, 24 V DC, 3000 K, IP 44	404.14	363.73
007-478	833.66.139	MODUL Q 64 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,9 W, 24 V DC, 3000 K, IP 44	577.17	519.45
007-497	833.66.140	MODUL Q 36 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6,8 W, 24 V DC, 3000 K, IP 44	378.73	340.86
007-713	833.66.141	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 750 lm, 8,3 W, 230 V AC, 50 Hz, 3000 K, IP 20	589.27	530.34
007-901	833.66.142	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 190 lm, 4,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	451.33	406.20
008-186	833.66.143	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 190 lm, 4,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	451.33	406.20

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
008-200	833.66.144	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 750 lm, 8.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	589.27	530.34
008-213	833.66.145	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 1 050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	755.04	679.54
008-214	833.66.146	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 1 050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	755.04	679.54
008-480	833.66.148	MODUL Q 100 AQUA, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18,1 W, 24 V DC, 3000 K, IP 44	723.58	651.22
008-768	833.66.154	ROXXANE, table clamp maximum clip opening 53 mm zinc	61.01	54.91
009-236	833.66.169	MODUL L 196, converter set cavity mounting switchable 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	72.60	65.34
009-281	833.66.170	MODUL L 196, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 3.800 lm, 27,5 W, 24 V DC, 3000 K, IP 20	1210.00	1089.00
009-282	833.66.171	MODUL L 196, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 3.300 lm, 23,5 W, 24 V DC, 3000 K, IP 20	1051.49	946.34
009-334	833.66.172	MODUL L 196, canopy direct mounting switchable, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	85.91	77.32

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
009-335	833.66.173	MODUL L 196, canopy direct mounting dimmable, DALI/switchDIM, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	252.89	227.60
009-336	833.66.174	MODUL L 196, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	164.56	148.10
009-442	833.66.175	CONVERTER capable for emergency lighting 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	146.41	131.77
009-464	833.66.176	CONVERTER switchable 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	238.37	214.53
009-565	833.66.177	MODUL Q 100 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18.1 W, 24 V DC, 3000 K, IP 44	699.38	629.44
009-943	833.66.178	L 120, canopy direct mounting dimmable, DALI/switchDIM white 50 Hz, IP 20	572.33	515.10
009-944	833.66.179	MODUL Q 100, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19.0 W, 24 V DC, 2700 K, IP 20	652.19	586.97
009-945	833.66.180	MODUL Q 100, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 17.3 W, 24 V DC, 4000 K, IP 20	652.19	586.97
009-946	833.66.181	MODUL Q 100, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19,0 W, 24 V DC, 2700 K, IP 20	684.86	616.37
009-947	833.66.182	MODUL Q 100, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 17,3 W, 24 V DC, 4000 K, IP 20	684.86	616.37

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
009-948	833.66.183	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 22.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	753.83	678.45
009-949	833.66.184	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 20.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	753.83	678.45
009-950	833.66.185	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment version for 24 V DC acrylic, satin-frosted CRI 90 2.150 lm, 19.0 W, 24 V DC, 2700 K, IP 20	701.80	631.62
009-951	833.66.186	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment version for 24 V DC acrylic, satin-frosted CRI 90 2.150 lm, 17.3 W, 24 V DC, 4000 K, IP 20	701.80	631.62
009-954	833.66.188	MODUL Q 144, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 23.3 W, 24 V DC, 4000 K, IP 20	892.98	803.68
009-956	833.66.190	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 27.1 W, 230 V AC, 50 Hz, 4000 K, IP 20	1197.90	1078.11
009-961	833.66.192	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment version for 24 V DC acrylic, satin-frosted CRI 90 3.000 lm, 23.3 W, 24 V DC, 4000 K, IP 20	951.06	855.95
009-964	833.66.194	MODUL Q 144, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 23,3 W, 24 V DC, 4000 K, IP 20	925.65	833.09
009-966	833.66.196	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment dimnable, 1-10 V, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 27.2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1351.57	1216.41

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
009-968	833.66.198	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 27,8 W, 230 V AC, 50 Hz, 4000 K, IP 20	1410.86	1269.77
009-979	833.66.199	MODUL Q 36, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7.1 W, 24 V DC, 2700 K, IP 20	257.73	231.96
009-980	833.66.200	MODUL Q 36, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6.5 W, 24 V DC, 4000 K, IP 20	257.73	231.96
009-981	833.66.201	MODUL Q 36 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7.1 W, 24 V DC, 2700 K, IP 44	353.32	317.99
009-983	833.66.203	MODUL Q 36, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7.1 W, 24 V DC, 2700 K, IP 20	273.46	246.11
009-984	833.66.204	MODUL Q 36, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6.5 W, 24 V DC, 4000 K, IP 20	273.46	246.11
009-985	833.66.205	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring stainless steel, brushed CRI 90 750 lm, 7.1 W, 24 V DC, 2700 K, IP 20	263.78	237.40
009-986	833.66.206	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring stainless steel, brushed CRI 90 750 lm, 6.5 W, 24 V DC, 4000 K, IP 20	263.78	237.40

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
009-990	833.66.207	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, white, brilliant, powder-coated CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	239.58	215.62
009-991	833.66.208	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, white, brilliant, powder-coated CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	239.58	215.62
009-992	833.66.209	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, silver, varnished CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	239.58	215.62
009-993	833.66.210	MODUL Q 36 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, silver, varnished CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	239.58	215.62
009-996	833.66.211	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with cavity bracket white, powder-coated CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	398.09	358.28
009-997	833.66.212	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with cavity bracket white, powder-coated CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	398.09	358.28
010-013	833.66.213	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with cavity bracket silver, varnished CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	398.09	358.28
010-014	833.66.214	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with cavity bracket silver, varnished CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	398.09	358.28

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-015	833.66.215	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	398.09	358.28
010-016	833.66.216	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	398.09	358.28
010-017	833.66.217	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring silver, varnished CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	398.09	358.28
010-018	833.66.218	MODUL Q 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring silver, varnished CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	398.09	358.28
010-023	833.66.219	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, silver, varnished CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	515.46	463.91
010-024	833.66.220	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, silver, varnished CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	515.46	463.91
010-025	833.66.221	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, white, varnished CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	515.46	463.91
010-026	833.66.222	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, white, varnished CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	515.46	463.91

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-031	833.66.223	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, silver, varnished CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	649.77	584.79
010-032	833.66.224	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, silver, varnished CRI 90 750 lm, 7.9 W, 230 V AC, 50 Hz, 4000 K, IP 20	649.77	584.79
010-033	833.66.225	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	649.77	584.79
010-034	833.66.226	MODUL Q 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 7.9 W, 230 V AC, 50 Hz, 4000 K, IP 20	649.77	584.79
010-035	833.66.227	MODUL Q 36 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 44	378.73	340.86
010-041	833.66.229	MODUL Q 49, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10.3 W, 24 V DC, 2700 K, IP 20	342.43	308.19
010-058	833.66.230	MODUL Q 49, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9.3 W, 24 V DC, 4000 K, IP 20	342.43	308.19
010-060	833.66.231	MODUL Q 49, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10,3 W, 24 V DC, 2700 K, IP 20	360.58	324.52

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-061	833.66.232	MODUL Q 49, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9,3 W, 24 V DC, 4000 K, IP 20	360.58	324.52
010-062	833.66.233	MODUL Q 49 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10,3 W, 24 V DC, 2700 K, IP 44	385.99	347.39
010-064	833.66.235	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 12,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	479.16	431.24
010-065	833.66.236	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	479.16	431.24
010-066	833.66.237	MODUL Q 49 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10,3 W, 24 V DC, 2700 K, IP 44	404.14	363.73
010-068	833.66.239	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13,6 W, 230 V AC, 50 Hz, 2700 K, IP 20	686.07	617.46
010-069	833.66.240	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 12,5 W, 230 V AC, 50 Hz, 4000 K, IP 20	686.07	617.46
010-073	833.66.241	MODUL Q 64, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	504.57	454.11
010-074	833.66.242	MODUL Q 64, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	504.57	454.11

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-075	833.66.243	MODUL Q 64 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 44	560.23	504.21
010-078	833.66.245	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring stainless steel, brushed CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	542.08	487.87
010-079	833.66.246	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring stainless steel, brushed CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	542.08	487.87
010-080	833.66.247	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, silver, varnished CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	523.93	471.54
010-081	833.66.248	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, silver, varnished CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	523.93	471.54
010-082	833.66.249	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, white, brilliant, powder-coated CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	523.93	471.54
010-083	833.66.250	MODUL Q 64 IN, ceiling luminaire cavity mounting, mounting depth in cavity 40 mm version for 24 V DC with mounting ring steel, white, brilliant, powder-coated CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	523.93	471.54
010-084	833.66.251	MODUL Q 64 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 44	577.17	519.45

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-086	833.66.253	MODUL Q 9, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.9 W, 24 V DC, 2700 K, IP 20	143.99	129.59
010-087	833.66.254	MODUL Q 9, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.6 W, 24 V DC, 4000 K, IP 20	143.99	129.59
010-088	833.66.255	MODUL Q 9 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.9 W, 24 V DC, 2700 K, IP 44	179.08	161.17
010-090	833.66.257	MODUL Q 64, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	523.93	471.54
010-091	833.66.258	MODUL Q 64, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	523.93	471.54
010-094	833.66.259	MODUL L 196, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 3.800 lm, 27,5 W, 24 V DC, 4000 K, IP 20	1210.00	1089.00
010-095	833.66.260	MODUL L 196, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 3.300 lm, 23,5 W, 24 V DC, 4000 K, IP 20	1051.49	946.34
010-152	833.66.279	MODUL R 100, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19.0 W, 24 V DC, 2700 K, IP 20	665.50	598.95

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-153	833.66.280	MODUL R 100, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 17,3 W, 24 V DC, 4000 K, IP 20	665.50	598.95
010-154	833.66.281	MODUL R 100, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19,0 W, 24 V DC, 2700 K, IP 20	701.80	631.62
010-161	833.66.282	MODUL R 100, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 17,3 W, 24 V DC, 4000 K, IP 20	701.80	631.62
010-162	833.66.283	MODUL R 100, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 22,5 W, 230 V AC, 50 Hz, 2700 K, IP 20	785.29	706.76
010-163	833.66.284	MODUL R 100, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 20,5 W, 230 V AC, 50 Hz, 4000 K, IP 20	785.29	706.76
010-193	833.66.286	MODUL R 144, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 23,3 W, 24 V DC, 4000 K, IP 20	925.65	833.09
010-195	833.66.288	MODUL R 144, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 3.000 lm, 23,3 W, 24 V DC, 4000 K, IP 20	960.74	864.67
010-198	833.66.290	MODUL R 144, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 27,1 W, 230 V AC, 50 Hz, 4000 K, IP 20	1213.63	1092.27

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-201	833.66.291	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	589.27	530.34
010-203	833.66.292	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	589.27	530.34
010-205	833.66.293	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 190 lm, 4.2 W, 230 V AC, 50 Hz, 2700 K, IP 20	451.33	406.20
010-207	833.66.294	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 190 lm, 4.2 W, 230 V AC, 50 Hz, 2700 K, IP 20	451.33	406.20
010-209	833.66.295	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 1 050 lm, 12.4 W, 230 V AC, 50 Hz, 2700 K, IP 20	755.04	679.54
010-211	833.66.296	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 1 050 lm, 12.4 W, 230 V AC, 50 Hz, 2700 K, IP 20	755.04	679.54
010-233	833.66.297	MODUL R 36, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7.1 W, 24 V DC, 2700 K, IP 20	257.73	231.96
010-236	833.66.298	MODUL R 36, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6.5 W, 24 V DC, 4000 K, IP 20	257.73	231.96

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-239	833.66.299	MODUL R 36, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	273.46	246.11
010-241	833.66.300	MODUL R 36, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	273.46	246.11
010-243	833.66.301	MODUL R 36, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 750 lm, 8,7 W, 230 V AC, 50 Hz, 2700 K, IP 20	436.81	393.13
010-251	833.66.302	MODUL R 36, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 750 lm, 7,9 W, 230 V AC, 50 Hz, 4000 K, IP 20	436.81	393.13
010-259	833.66.303	MODUL R 36 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 44	353.32	317.99
010-271	833.66.305	MODUL R 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	398.09	358.28
010-272	833.66.306	MODUL R 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	398.09	358.28
010-277	833.66.307	MODUL R 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	515.46	463.91

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-278	833.66.308	MODUL R 36 TT, ceiling luminaire with surface-mounted housing version for 24 V DC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 6.5 W, 24 V DC, 4000 K, IP 20	515.46	463.91
010-283	833.66.309	MODUL R 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	649.77	584.79
010-284	833.66.310	MODUL R 36 TT, ceiling luminaire with surface-mounted housing switchable, version for 230 V AC rotatable and tiltable steel, white, powder-coated CRI 90 750 lm, 7.9 W, 230 V AC, 50 Hz, 4000 K, IP 20	649.77	584.79
010-289	833.66.311	MODUL R 36 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 44	369.05	332.15
010-331	833.66.313	MODUL R 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 7,1 W, 24 V DC, 2700 K, IP 20	398.09	358.28
010-333	833.66.314	MODUL R 36 TT, ceiling luminaire cavity mounting / HaloX-O, mounting depth in cavity 40 mm version for 24 V DC rotatable and tiltable with mounting ring white, powder-coated CRI 90 750 lm, 6,5 W, 24 V DC, 4000 K, IP 20	398.09	358.28
010-348	833.66.315	MODUL R 49, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10.3 W, 24 V DC, 2700 K, IP 20	378.73	340.86
010-349	833.66.316	MODUL R 49, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9.3 W, 24 V DC, 4000 K, IP 20	378.73	340.86

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-350	833.66.317	MODUL R 49, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10,3 W, 24 V DC, 2700 K, IP 20	392.04	352.84
010-351	833.66.318	MODUL R 49, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 9,3 W, 24 V DC, 4000 K, IP 20	392.04	352.84
010-355	833.66.319	MODUL R 49, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 12,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	515.46	463.91
010-357	833.66.320	MODUL R 49, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	515.46	463.91
010-361	833.66.321	MODUL R 49 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10,3 W, 24 V DC, 2700 K, IP 44	423.50	381.15
010-365	833.66.323	MODUL R 49 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.050 lm, 10,3 W, 24 V DC, 2700 K, IP 44	438.02	394.22
010-369	833.66.325	MODUL R 64, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	539.66	485.69
010-370	833.66.326	MODUL R 64, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	539.66	485.69

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-372	833.66.327	MODUL R 64, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 20	559.02	503.12
010-373	833.66.328	MODUL R 64, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 10,5 W, 24 V DC, 4000 K, IP 20	559.02	503.12
010-375	833.66.329	MODUL R 64, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13.6 W, 230 V AC, 50 Hz, 2700 K, IP 20	719.95	647.96
010-377	833.66.330	MODUL R 64, ceiling luminaire with surface-mounted housing, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 12.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	719.95	647.96
010-383	833.66.331	MODUL R 64 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11.5 W, 24 V DC, 2700 K, IP 44	577.17	519.45
010-385	833.66.333	MODUL R 64 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 1.350 lm, 11,5 W, 24 V DC, 2700 K, IP 44	595.32	535.79
010-387	833.66.335	MODUL R 9, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.9 W, 24 V DC, 2700 K, IP 20	143.99	129.59
010-388	833.66.336	MODUL R 9, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2.6 W, 24 V DC, 4000 K, IP 20	143.99	129.59

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-389	833.66.337	MODUL R 9, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,9 W, 24 V DC, 2700 K, IP 20	171.82	154.64
010-390	833.66.338	ZEN IN S, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 55 lm, 1.5 W, 24 V DC, 2700 K, IP 20	168.19	151.37
010-391	833.66.339	MODUL R 9, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,6 W, 24 V DC, 4000 K, IP 20	171.82	154.64
010-398	833.66.340	ZEN IN S, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 55 lm, 1.5 W, 24 V DC, 2700 K, IP 20	168.19	151.37
010-399	833.66.341	MODUL R 9 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,9 W, 24 V DC, 2700 K, IP 44	189.97	170.97
010-400	833.66.342	ZEN IN M LONG POWER, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 340 lm, 6,0 W, 24 V DC, 2700 K, IP 20	290.40	261.36
010-402	833.66.344	MODUL R 9 AQUA, ceiling luminaire cavity mounting / HaloX-O, with magnetic attachment, mounting depth in cavity 40 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 190 lm, 2,9 W, 24 V DC, 2700 K, IP 44	217.80	196.02
010-403	833.66.345	ZEN IN M LONG POWER, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 6,0 W, 24 V DC, 2700 K, IP 20	290.40	261.36

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-407	833.66.347	ZEN IN M, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 85 lm, 1.5 W, 24 V DC, 2700 K, IP 20	202.07	181.86
010-408	833.66.348	ZEN IN M LONG, wall luminaire, near-ground cavity mounting version for 24 V DC aluminium, anodised CRI 80 170 lm, 3.0 W, 24 V DC, 2700 K, IP 20	251.68	226.51
010-409	833.66.349	ZEN IN M, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 85 lm, 1.5 W, 24 V DC, 2700 K, IP 20	202.07	181.86
010-410	833.66.350	ZEN IN M LONG, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC aluminium, anodised CRI 80 170 lm, 3.0 W, 24 V DC, 2700 K, IP 20	251.68	226.51
010-411	833.66.351	ZEN ON, wall luminaire, near-ground with wall mounting set version for 24 V DC aluminium, anodised CRI 80 85 lm, 1.5 W, 24 V DC, 2700 K, IP 20	217.80	196.02
010-412	833.66.352	ZEN ON LONG, wall luminaire, near-ground with wall mounting set version for 24 V DC aluminium, anodised CRI 80 170 lm, 3.0 W, 24 V DC, 2700 K, IP 20	251.68	226.51
010-413	833.66.353	MIKE INDIA 70 ACCENT, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 140 lm, 3,0 W, 24 V DC, 2700 K, IP 20	198.44	178.60
010-414	833.66.354	MIKE INDIA 70 ACCENT, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 140 lm, 3,0 W, 24 V DC, 2700 K, IP 20	198.44	178.60
010-415	833.66.355	MIKE INDIA 70 ACCENT LONG, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 280 lm, 6,0 W, 24 V DC, 2700 K, IP 20	257.73	231.96

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
010-416	833.66.356	MIKE INDIA 70 ACCENT LONG, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 280 lm, 6,0 W, 24 V DC, 2700 K, IP 20	257.73	231.96
010-419	833.66.357	MIKE INDIA 50 ACCENT, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 55 lm, 1,5 W, 24 V DC, 2700 K, IP 20	170.61	153.55
010-422	833.66.359	MIKE INDIA 50 ACCENT LONG, wall luminaire, near-ground cavity mounting, mounting depth in cavity 30 mm version for 24 V DC stainless steel, brushed CRI 80 110 lm, 3,0 W, 24 V DC, 2700 K, IP 20	198.44	178.60
010-425	833.66.360	MIKE INDIA 50 ACCENT, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 55 lm, 1,5 W, 24 V DC, 2700 K, IP 20	170.61	153.55
010-428	833.66.362	MIKE INDIA 50 ACCENT LONG, wall luminaire, near-ground for flushmounted install. kit version for 24 V DC stainless steel, brushed CRI 80 110 lm, 3,0 W, 24 V DC, 2700 K, IP 20	198.44	178.60
010-613	833.66.385	MODUL L 196, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 3.800 lm, 27,5 W, 24 V DC, 2700 K, IP 20	1210.00	1089.00
010-614	833.66.386	MODUL L 196, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 3.300 lm, 23,5 W, 24 V DC, 2700 K, IP 20	1051.49	946.34
544-109	833.66.387	ROXXANE, adapter USM Haller table leg for USM Haller Table, for USM Haller Table Plus, for USM Haller Table advanced	61.01	54.91
544-110	833.67.276	ROXXANE, universal adapter table mounting	45.76	41.19

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
544-752	833.66.390	MODUL L 112, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 2000 mm with suspension kit aluminium, anodised CRI 80 1.860 lm, 14,0 W, 24 V DC, 2700 K, IP 20	805.86	725.27
544-768	833.66.391	ROXXANE, wall bracket/wall suspension with wall mounting set	76.27	68.64
544-769	833.66.392	ROXXANE, adapter USM adaptation point for USM Haller Table Plus, for USM Haller Table advanced, for USM Kitos E Plus Table, for USM Kitos E Advanced Table NP	61.01	54.91
544-819	833.66.393	MODUL L 112, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 2000 mm with suspension kit aluminium, anodised CRI 80 1.860 lm, 14,0 W, 24 V DC, 3000 K, IP 20	805.86	725.27
544-820	833.66.394	MODUL L 112, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 2000 mm with suspension kit aluminium, anodised CRI 80 1.860 lm, 14,0 W, 24 V DC, 4000 K, IP 20	805.86	725.27
544-822	833.66.395	MODUL L 112, canopy direct mounting switchable, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	85.91	77.32
544-824	833.66.396	MODUL L 112, canopy direct mounting dimnable, 1-10 V, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	164.56	148.10
544-825	833.66.397	MODUL L 112, canopy direct mounting dimnable, DALI/switchDIM, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	252.89	227.60
544-826	833.66.398	MODUL L 112, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 2000 mm with suspension kit aluminium, anodised CRI 80 2.110 lm, 16,0 W, 24 V DC, 2700 K, IP 20	909.92	818.93

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
544-827	833.66.399	MODUL L 112, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 2000 mm with suspension kit aluminium, anodised CRI 80 2.110 lm, 16,0 W, 24 V DC, 3000 K, IP 20	909.92	818.93
544-828	833.66.400	MODUL L 112, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 2000 mm with suspension kit aluminium, anodised CRI 80 2.110 lm, 16,0 W, 24 V DC, 4000 K, IP 20	909.92	818.93
544-829	833.66.401	MODUL L 196, ceiling luminaire for surface-mounted housing version for 24 V DC aluminium, anodised CRI 80 3.300 lm, 23.5 W, 24 V DC, 3000 K, IP 20	1051.49	946.34
544-830	833.66.402	MODUL L 196, ceiling luminaire for surface-mounted housing version for 24 V DC aluminium, anodised CRI 80 3.300 lm, 23.5 W, 24 V DC, 2700 K, IP 20	1051.49	946.34
544-831	833.66.403	MODUL L 196, ceiling luminaire for surface-mounted housing version for 24 V DC aluminium, anodised CRI 80 3.300 lm, 23.5 W, 24 V DC, 4000 K, IP 20	1051.49	946.34
544-832	833.66.404	MODUL L 196, surface-mounted housing direct mounting switchable, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	85.91	77.32
544-833	833.66.405	MODUL L 196, surface-mounted housing direct mounting dimmable, 1-10 V, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	164.56	148.10
544-834	833.66.406	MODUL L 196, surface-mounted housing direct mounting dimmable, DALI/switchDIM, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	252.89	227.60
544-835	833.66.407	MODUL L 196, ceiling luminaire direct mounting version for 24 V DC with mounting plate aluminium, anodised CRI 80 3.300 lm, 23.5 W, 24 V DC, 3000 K, IP 20	1051.49	946.34

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
544-836	833.66.408	MODUL L 196, ceiling luminaire direct mounting version for 24 V DC with mounting plate aluminium, anodised CRI 80 3.300 lm, 23.5 W, 24 V DC, 2700 K, IP 20	1051.49	946.34
544-837	833.66.409	MODUL L 196, ceiling luminaire direct mounting version for 24 V DC with mounting plate aluminium, anodised CRI 80 3.300 lm, 23.5 W, 24 V DC, 4000 K, IP 20	1051.49	946.34
544-929	833.66.410	MODUL Q 100 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19,0 W, 24 V DC, 2700 K, IP 44	699.38	629.44
544-931	833.66.412	MODUL Q 100 AQUA, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19,0 W, 24 V DC, 2700 K, IP 44	723.58	651.22
544-952	833.66.414	MODUL R 100 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18.1 W, 24 V DC, 3000 K, IP 44	713.90	642.51
544-953	833.66.415	MODUL R 100 AQUA, ceiling luminaire direct mounting, with magnetic attachment version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19,0 W, 24 V DC, 2700 K, IP 44	713.90	642.51
544-955	833.66.417	MODUL R 100 AQUA, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 18,1 W, 24 V DC, 3000 K, IP 44	738.10	664.29
544-957	833.66.419	MODUL R 100 AQUA, ceiling luminaire cavity mounting, with magnetic attachment, mounting depth in cavity 90 mm version for 24 V DC with mounting ring acrylic, satin-frosted CRI 90 2.150 lm, 19,0 W, 24 V DC, 2700 K, IP 44	738.10	664.29

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
545-632	833.66.420	MODUL L 196 S3, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 9.900 lm, 70,5 W, 24 V DC, 3000 K, IP 20	3452.13	3106.92
545-633	833.66.421	MODUL L 196 S2, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 6.600 lm, 47,0 W, 24 V DC, 3000 K, IP 20	2249.39	2024.45
545-672	833.66.422	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 190 lm, 4.2 W, 230 V AC, 50 Hz, 2700 K, IP 20	572.33	515.10
545-673	833.66.423	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 190 lm, 4.2 W, 230 V AC, 50 Hz, 2700 K, IP 20	451.33	406.20
545-674	833.66.424	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 190 lm, 4.2 W, 230 V AC, 50 Hz, 2700 K, IP 20	451.33	406.20
545-675	833.66.425	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 190 lm, 4.2 W, 230 V AC, 50 Hz, 2700 K, IP 20	451.33	406.20
545-676	833.66.426	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 190 lm, 4.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	572.33	515.10
545-677	833.66.427	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 190 lm, 4.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	451.33	406.20

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
545-678		RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 190 lm, 4.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	451.33	406.20
545-679	833.66.429	RIM R 9, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 190 lm, 4.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	451.33	406.20
545-702	833.66.430	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 1 050 lm, 12.4 W, 230 V AC, 50 Hz, 2700 K, IP 20	906.29	815.66
545-703	833.66.431	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 1 050 lm, 12.4 W, 230 V AC, 50 Hz, 2700 K, IP 20	755.04	679.54
545-705	833.66.433	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 1 050 lm, 12.4 W, 230 V AC, 50 Hz, 2700 K, IP 20	755.04	679.54
545-706		RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 1 050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	906.29	815.66
545-707	833.66.435	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 1 050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	755.04	679.54
545-708	833.66.436	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 1 050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	755.04	679.54

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
545-709	833.66.437	RIM R 49, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 1.050 lm, 11.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	755.04	679.54
545-716	833.66.438	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	724.79	652.31
545-717	833.66.439	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	589.27	530.34
545-718		RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	589.27	530.34
545-719	833.66.441	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 750 lm, 8.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	589.27	530.34
545-720	833.66.442	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 750 lm, 8.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	724.79	652.31
545-721	833.66.443	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 750 lm, 8.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	589.27	530.34
545-722	833.66.444	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 750 lm, 8.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	589.27	530.34

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
545-723	833.66.445	RIM R 36, ceiling luminaire for ceiling mounting switchable, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 750 lm, 8,3 W, 230 V AC, 50 Hz, 3000 K, IP 20	589.27	530.34
545-850	833.66.446	MODUL L 196 S2, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 6.600 lm, 47,0 W, 24 V DC, 2700 K, IP 20	2249.39	2024.45
545-852	833.66.447	MODUL L 196 S2, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 6.600 lm, 47,0 W, 24 V DC, 4000 K, IP 20	2249.39	2024.45
545-853	833.66.448	MODUL L 196 S2, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 7.600 lm, 55,0 W, 24 V DC, 2700 K, IP 20	2570.04	2313.04
545-854	833.66.449	MODUL L 196 S2, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 7.600 lm, 55,0 W, 24 V DC, 3000 K, IP 20	2570.04	2313.04
545-855	833.66.450	MODUL L 196 S2, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 7.600 lm, 55,0 W, 24 V DC, 4000 K, IP 20	2570.04	2313.04
545-856	833.66.451	MODUL L 196 S3, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 9.900 lm, 70,5 W, 24 V DC, 2700 K, IP 20	3452.13	3106.92

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
545-858	833.66.452	MODUL L 196 S3, suspended luminaire suspended mounting version for 24 V DC single-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 9.900 lm, 70,5 W, 24 V DC, 4000 K, IP 20	3452.13	3106.92
545-859	833.66.453	MODUL L 196 S3, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 11.400 lm, 82,5 W, 24 V DC, 2700 K, IP 20	3928.87	3535.98
545-860	833.66.454	MODUL L 196 S3, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 11.400 lm, 82,5 W, 24 V DC, 3000 K, IP 20	3928.87	3535.98
545-861	833.66.455	MODUL L 196 S3, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 11.400 lm, 82,5 W, 24 V DC, 4000 K, IP 20	3928.87	3535.98
545-864	833.66.456	MODUL L 196 S2, canopy direct mounting switchable, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 100 W, IP 20	208.12	187.31
545-865	833.66.457	MODUL L 196 S2, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 100 W, IP 20	285.56	257.00
545-866	833.66.458	MODUL L 196 S2, canopy direct mounting dimmable, DALI/switchDIM, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 100 W, IP 20	377.52	339.77
545-869	833.66.459	MODUL L 196 S3, canopy direct mounting switchable, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 96 W, IP 20	413.82	372.44
545-870	833.66.460	MODUL L 196 S3, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 96 W, IP 20	503.36	453.02

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
545-871	833.66.461	MODUL L 196 S3, canopy direct mounting dimmable, DALI, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 96 W, IP 20	546.92	492.23
546-161	833.66.464	L 120, suspended luminaire suspended mounting with gesture-controlled dimmer, version for 24 V DC max. suspended length 1800 mm with suspension kit aluminium, chrome plated CRI 80 1 826 lm, 26.0 W, 24 V DC, 3000 K, IP 20	1292.28	1163.05
546-166	833.67.264	CONVERTER switchable 230 V AC, 50 Hz, output 24 V DC, 3 W NP	44.77	40.29
546-280		PWM DIMMING UNIT with potentiometer 24 V DC, output 24 V DC, 120 W, IP 20	122.21	109.99
546-579	833.66.468	MODUL Q PROJECT 600, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 4 300 lm, 39.0 W, 24 V DC, 3000 K, IP 20	1539.12	1385.21
546-613	833.66.469	MODUL Q PROJECT 900, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 7 120 lm, 66.0 W, 24 V DC, 3000 K, IP 20	2541.00	2286.90
546-614	833.66.470	MODUL Q PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 12 484 lm, 115.0 W, 24 V DC, 3000 K, IP 20	4484.26	4035.83
546-650	833.66.471	MODUL L 112, surface-mounted housing direct mounting dimmable, 1-10 V, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	164.56	148.10
546-651	833.66.472	MODUL L 112, ceiling luminaire for surface-mounted housing version for 24 V DC aluminium, anodised CRI 80 1 860 lm, 14.0 W, 24 V DC, 3000 K, IP 20	805.86	725.27
546-735	833.66.474	MODUL Q PROJECT 600, canopy direct mounting dimmable, DALI/switchDIM, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	377.52	339.77

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
546-736	833.66.475	MODUL Q PROJECT 900, canopy direct mounting dimmable, DALI/switchDIM, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	377.52	339.77
546-740	833.66.476	MODUL Q PROJECT 1200, canopy direct mounting dimmable, DALI, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	680.02	612.02
546-767	833.66.477	MODUL Q PROJECT 600/900/1200, suspension kit for ceiling mounting max. suspended length 2000 mm with 24 V supply cord stainless steel	128.26	115.43
546-768	833.66.478	MODUL Q PROJECT 600/900/1200, suspension kit for ceiling mounting max. suspended length 4000 mm with 24 V supply cord stainless steel	141.57	127.41
546-829	833.66.480	MODUL Q PROJECT 600, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 3 655 lm 32.0 W 24 V DC 3000 K IP 20	1367.30	1230.57
546-830	833.66.481	MODUL Q PROJECT 600, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 3 655 lm 32.0 W 24 V DC 4000 K IP 20	1367.30	1230.57
546-832	833.66.482	MODUL Q PROJECT 600, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 4 300 lm 39.0 W 24 V DC 4000 K IP 20	1539.12	1385.21
546-834	833.66.483	MODUL Q PROJECT 900, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 6 475 lm 59.0 W 24 V DC 3000 K IP 20	2371.60	2134.44
546-835	833.66.484	MODUL Q PROJECT 900, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 6 475 lm 59.0 W 24 V DC 4000 K IP 20	2371.60	2134.44

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
546-837	833.66.485	MODUL Q PROJECT 900, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 7 120 lm, 66.0 W, 24 V DC, 4000 K, IP 20	2541.00	2286.90
546-839	833.66.486	MODUL Q PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 11 839 lm, 108.0 W, 24 V DC, 3000 K, IP 20	4316.07	3884.46
546-840	833.66.487	MODUL Q PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 11 839 lm, 108.0 W, 24 V DC, 4000 K, IP 20	4316.07	3884.46
546-842	833.66.488	MODUL Q PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 12 484 lm, 115.0 W, 24 V DC, 4000 K, IP 20	4484.26	4035.83
546-843	833.66.489	MODUL Q PROJECT 600, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	285.56	257.00
546-844	833.66.490	MODUL Q PROJECT 600, canopy direct mounting switchable, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	208.12	187.31
546-845	833.66.491	MODUL Q PROJECT 900, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	285.56	257.00
546-846	833.66.492	MODUL Q PROJECT 900, canopy direct mounting switchable, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	208.12	187.31
546-847	833.66.493	MODUL Q PROJECT 1200, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	618.31	556.48
546-848	833.66.494	MODUL Q PROJECT 1200, canopy direct mounting switchable, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	413.82	372.44

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
546-881	833.66.497	MODUL L 112, surface-mounted housing direct mounting switchable, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	85.91	77.32
546-882	833.66.498	MODUL L 112, surface-mounted housing direct mounting dimmable, DALI/switchDIM, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	252.89	227.60
546-906	833.66.499	MODUL L 112, ceiling luminaire for surface-mounted housing version for 24 V DC aluminium, anodised CRI 80 1.860 lm, 14.0 W, 24 V DC, 4000 K, IP 20	805.86	725.27
546-908	833.66.500	MODUL L 112, ceiling luminaire for surface-mounted housing version for 24 V DC aluminium, anodised CRI 80 1.860 lm, 14.0 W, 24 V DC, 2700 K, IP 20	805.86	725.27
547-062	833.66.502	MODUL L 112, ceiling luminaire direct mounting version for 24 V DC aluminium, anodised CRI 80 1.860 lm, 14.0 W, 24 V DC, 3000 K, IP 20	805.86	725.27
547-064	833.66.503	MODUL L 112, ceiling luminaire direct mounting version for 24 V DC aluminium, anodised CRI 80 1.860 lm, 14.0 W, 24 V DC, 4000 K, IP 20	805.86	725.27
547-066	833.66.504	MODUL L 112, ceiling luminaire direct mounting version for 24 V DC aluminium, anodised CRI 80 1.860 lm, 14.0 W, 24 V DC, 2700 K, IP 20	805.86	725.27
547-208	833.66.505	FORCE ONE, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, brilliant, polished CRI 80 6.246 lm, 58,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	2845.92	2561.33
547-209	833.66.506	FORCE ONE, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, brilliant, polished CRI 80 6.246 lm, 58,0 W, 230 V AC, 50 Hz, 4000 K, IP 20	2845.92	2561.33
547-211	833.66.507	FORCE ONE, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, matt, anodised CRI 80 6.246 lm, 58,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	2432.10	2188.89

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
547-212	833.66.508	FORCE ONE, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, matt, anodised CRI 80 6.246 lm, 58,0 W, 230 V AC, 50 Hz, 4000 K, IP 20	2432.10	2188.89
547-214	833.66.509	FORCE ONE, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, white, brilliant, powder-coated CRI 80 6.246 lm, 58,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	2210.67	1989.60
547-215	833.66.510	FORCE ONE, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, white, brilliant, powder-coated CRI 80 6.246 lm, 58,0 W, 230 V AC, 50 Hz, 4000 K, IP 20	2210.67	1989.60
547-233	833.66.511	FORCE ONE POWER, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, white, brilliant, powder-coated CRI 80 8.472 lm, 75,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	2432.10	2188.89
547-234	833.66.512	FORCE ONE POWER, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, white, brilliant, powder-coated CRI 80 8.472 lm, 75,0 W, 230 V AC, 50 Hz, 4000 K, IP 20	2432.10	2188.89
547-236	833.66.513	FORCE ONE POWER, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, matt, anodised CRI 80 8.472 lm, 75,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	2653.53	2388.18
547-237	833.66.514	FORCE ONE POWER, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, matt, anodised CRI 80 8.472 lm, 75,0 W, 230 V AC, 50 Hz, 4000 K, IP 20	2653.53	2388.18
547-239	833.66.515	FORCE ONE POWER, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, brilliant, polished CRI 80 8.472 lm, 75,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	3068.56	2761.70
547-240	833.66.516	FORCE ONE POWER, floorstanding luminaire with presence and light sensor, capable for video conferencing aluminium, brilliant, polished CRI 80 8.472 lm, 75,0 W, 230 V AC, 50 Hz, 4000 K, IP 20	3068.56	2761.70
547-401	833.66.520	COMBI CONVERTER, converter set with CASAMBI control, version for 230 V AC 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	277.09	249.38
547-402	833.66.521	COMBI CONVERTER, converter set with CASAMBI control, version for 230 V AC 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	323.07	290.76
547-403	833.66.522	COMBI CONVERTER, converter set with CASAMBI control, version for 230 V AC 230 V AC, 50 Hz, output 24 V DC, 100 W, IP 20	444.07	399.66
547-416	833.66.523	PWM DIMMING UNIT, control unit with CASAMBI control 120,0 W, 24 V DC, output 24 V DC, 120 W, IP 20	245.63	221.07

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
547-564	833.66.524	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	723.58	651.22
547-570	833.66.525	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	723.58	651.22
547-572	833.66.526	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11.4 W, 230 V AC, 50 Hz, 4000 K, IP 20	723.58	651.22
547-583	833.66.527	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	930.49	837.44
547-584	833.66.528	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	930.49	837.44
547-585	833.66.529	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 12.6 W, 230 V AC, 50 Hz, 4000 K, IP 20	930.49	837.44
547-596	833.66.530	MODUL R 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	758.67	682.80
547-597	833.66.531	MODUL R 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11.4 W, 230 V AC, 50 Hz, 4000 K, IP 20	758.67	682.80
547-598	833.66.532	MODUL R 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	758.67	682.80
547-602	833.66.533	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 21.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	997.04	897.34

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
547-603	833.66.534	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 22.6 W, 230 V AC, 50 Hz, 2700 K, IP 20	997.04	897.34
547-604	833.66.535	MODUL Q 100, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 20.6 W, 230 V AC, 50 Hz, 4000 K, IP 20	997.04	897.34
547-606	833.66.536	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 28.4 W, 230 V AC, 50 Hz, 3000 K, IP 20	1442.32	1298.09
547-608	833.66.538	MODUL Q 144, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 27.2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1442.32	1298.09
547-617	833.66.539	MODUL R 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	964.37	867.93
547-700	833.66.540	MODUL L 112, canopy direct mounting with CASAMBI control, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 30 W, IP 20	330.33	297.30
547-708	833.66.541	MODUL L 196, canopy direct mounting with CASAMBI control, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	330.33	297.30
547-741	833.66.542	MODUL R 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 12.6 W, 230 V AC, 50 Hz, 4000 K, IP 20	964.37	867.93
547-742	833.66.543	MODUL R 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13.7 W, 230 V AC, 50 Hz, 2700 K, IP 20	964.37	867.93
547-749	833.66.544	MODUL R 100, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 21.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	1029.71	926.74

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
547-750	833.66.545	MODUL R 100, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 20.6 W, 230 V AC, 50 Hz, 4000 K, IP 20	1029.71	926.74
547-751	833.66.546	MODUL R 100, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 2.150 lm, 22.6 W, 230 V AC, 50 Hz, 2700 K, IP 20	1029.71	926.74
547-765	833.66.547	MODUL R 144, ceiling luminaire with surface-mounted housing, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 90 3.000 lm, 28.4 W, 230 V AC, 50 Hz, 3000 K, IP 20	1456.84	1311.16
547-810	833.66.549	MODUL L 196, surface-mounted housing direct mounting with CASAMBI control, version for 230 V AC white 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	330.33	297.30
547-825	833.66.550	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	1150.71	1035.64
547-826	833.66.551	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, brilliant, chrome plated CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	1150.71	1035.64
547-828	833.66.552	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	998.25	898.43
547-829	833.66.553	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, gold, matt, anodised CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	998.25	898.43
547-831	833.66.554	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	998.25	898.43

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
547-832	833.66.555	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, graphite black, matt, anodised CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	998.25	898.43
547-834	833.66.556	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	998.25	898.43
547-835	833.66.557	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, frosted silver, matt, anodised CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	998.25	898.43
547-841	833.66.558	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, titanium grey, matt, anodised CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	998.25	898.43
547-844	833.66.559	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 1.050 lm, 12.5 W, 230 V AC, 50 Hz, 2700 K, IP 20	998.25	898.43
547-845	833.66.560	RIM R 49, ceiling luminaire for ceiling mounting with CASAMBI control, version for 230 V AC rotatable and tiltable aluminium, white, brilliant, powder-coated CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	998.25	898.43
548-686	833.66.561	MODUL R PROJECT 600, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 4.361 lm, 41.0 W, 24 V DC, 3000 K, IP 20	1415.35	1453.82
548-687	833.66.562	MODUL R PROJECT 600, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 3.473 lm, 33.0 W, 24 V DC, 3000 K, IP 20	1438.69	1294.82

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
548-688	833.66.563	MODUL R PROJECT 900, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 7 484 lm, 68.0 W, 24 V DC, 3000 K, IP 20	2668.05	2401.25
548-689	833.66.564	MODUL R PROJECT 900, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 6 596 lm, 60.0 W, 24 V DC, 3000 K, IP 20	2491.39	2242.25
548-690	833.66.565	MODUL R PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 11 932 lm, 107.0 W, 24 V DC, 3000 K, IP 20	4708.11	4237.30
548-691	833.66.566	MODUL R PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 11 044 lm, 99.0 W, 24 V DC, 3000 K, IP 20	4533.87	4080.48
549-489	833.66.567	MODUL R PROJECT 600/900/1200, suspension kit for ceiling mounting max. suspended length 2000 mm with 24 V supply cord stainless steel	100.43	90.39
549-490	833.66.568	MODUL R PROJECT 600/900/1200, suspension kit for ceiling mounting max. suspended length 4000 mm with 24 V supply cord stainless steel	110.11	99.10
549-491	833.66.569	MODUL R PROJECT 600, canopy direct mounting dimmable, DALI/switchDIM, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	377.52	339.77
549-492	833.66.570	MODUL R PROJECT 900, canopy direct mounting dimmable, DALI/switchDIM, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	377.52	339.77
549-493	833.66.571	MODUL R PROJECT 1200, canopy direct mounting dimmable, DALI, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	680.02	612.02

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
549-720	833.66.572	custom-made product MODUL Q PROJECT 600, canopy direct mounting with CASAMBI control, version for 230 V AC white, brilliant <u>230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20</u>	452.54	407.29
549-863	833.66.573	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 <u>1.200 lm, 8.9 W, 24 V DC, 3000 K, IP 20</u>	370.26	333.23
549-864	833.66.574	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 <u>1.200 lm, 8.8 W, 24 V DC, 4000 K, IP 20</u>	370.26	333.23
549-866	833.66.575	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 <u>1.800 lm, 13.8 W, 24 V DC, 3000 K, IP 20</u>	563.86	507.47
549-867	833.66.576	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 <u>1.800 lm, 13.6 W, 24 V DC, 4000 K, IP 20</u>	563.86	507.47
549-893	833.66.577	MODUL R PROJECT 600, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white, brilliant <u>230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20</u>	285.56	257.00
549-895	833.66.578	MODUL R PROJECT 900, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white, brilliant <u>230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20</u>	285.56	257.00
549-896	833.66.579	MODUL R PROJECT 1200, canopy direct mounting dimmable, 1-10 V, version for 230 V AC white, brilliant <u>230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20</u>	618.31	556.48
549-897	833.66.580	MODUL R PROJECT 600, canopy direct mounting switchable, version for 230 V AC white, brilliant <u>230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20</u>	208.12	187.31
549-898	833.66.581	MODUL R PROJECT 900, canopy direct mounting switchable, version for 230 V AC white, brilliant <u>230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20</u>	208.12	187.31

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
549-899	833.66.582	MODUL R PROJECT 1200, canopy direct mounting switchable, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	413.82	372.44
550-134	833.66.583	MODUL R PROJECT 600, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 4 361 lm 41.0 W 24 V DC 4000 K IP 20	1615.35	1453.82
550-137	833.66.584	MODUL R PROJECT 600, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 3 473 lm 33.0 W 24 V DC 4000 K IP 20	1438.69	1294.82
550-139	833.66.585	MODUL R PROJECT 900, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 7 484 lm 68.0 W 24 V DC 4000 K IP 20	2668.05	2401.25
550-142	833.66.586	MODUL R PROJECT 900, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 6 596 lm 60.0 W 24 V DC 4000 K IP 20	2491.39	2242.25
550-144	833.66.587	MODUL R PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC double-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 11 932 lm 107.0 W 24 V DC 4000 K IP 20	4708.11	4237.30
550-146	833.66.588	MODUL R PROJECT 1200, suspended luminaire suspended mounting version for 24 V DC single-sided without suspension kit, without 24 V supply cord acrylic, satin-frosted CRI 80 11 044 lm 99.0 W 24 V DC 4000 K IP 20	4533.87	4080.48
550-183	833.66.589	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1 200 lm 10.9 W 230 V AC 50 Hz 3000 K IP 20	473.11	425.80

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
550-185	833.66.590	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20	473.11	425.80
550-186	833.66.591	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,9 W, 230 V AC, 50 Hz, 3000 K, IP 20	652.19	586.97
550-188	833.66.592	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20	652.19	586.97
550-195	833.66.593	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16,5 W, 230 V AC, 50 Hz, 3000 K, IP 20	840.95	756.86
550-197	833.66.594	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	840.95	756.86
550-198	833.66.595	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16,5 W, 230 V AC, 50 Hz, 3000 K, IP 20	665.50	598.95
550-200	833.66.596	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	665.50	598.95
550-201	833.66.597	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,9 W, 230 V AC, 50 Hz, 3000 K, IP 20	630.41	567.37

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
550-203	833.66.598	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	630.41	567.37
550-204	833.66.599	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	716.32	644.69
550-206	833.66.600	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	716.32	644.69
550-207	833.66.601	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16.5 W, 230 V AC, 50 Hz, 3000 K, IP 20	822.80	740.52
550-209	833.66.602	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16.4 W, 230 V AC, 50 Hz, 4000 K, IP 20	822.80	740.52
550-210	833.66.603	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16.5 W, 230 V AC, 50 Hz, 3000 K, IP 20	909.92	818.93
550-212	833.66.604	MODUL Q PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16.4 W, 230 V AC, 50 Hz, 4000 K, IP 20	909.92	818.93
550-354	833.66.605	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9.2 W, 24 V DC, 3000 K, IP 20	444.07	399.66

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
550-356	833.66.606	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,1 W, 24 V DC, 3000 K, IP 20	607.42	546.68
550-440	833.66.607	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,9 W, 24 V DC, 3000 K, IP 20	528.77	475.89
550-442	833.66.608	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,8 W, 24 V DC, 4000 K, IP 20	528.77	475.89
550-443	833.66.609	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,9 W, 24 V DC, 3000 K, IP 20	556.60	500.94
550-447	833.66.610	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,8 W, 24 V DC, 4000 K, IP 20	556.60	500.94
550-471	833.66.611	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,8 W, 24 V DC, 3000 K, IP 20	719.95	647.96
550-473	833.66.612	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,6 W, 24 V DC, 4000 K, IP 20	719.95	647.96
550-474	833.66.613	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,8 W, 24 V DC, 3000 K, IP 20	748.99	674.09

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
550-476	833.66.614	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,6 W, 24 V DC, 4000 K, IP 20	748.99	674.09
550-618	833.66.615	CONVERTER capable for emergency lighting 230 V AC, 50 Hz, output 24 V DC, 12 W, IP 20 NP	68.97	62.07
550-842	833.66.616	CONVERTER capable for emergency lighting 230 V AC, 0/50/60 Hz, output 24 V DC, 60 W, IP 20	157.30	141.57
550-843	833.66.617	CONVERTER capable for emergency lighting 230 V AC, 0/50/60 Hz, output 24 V DC, 35 W, IP 20 NP	123.42	111.08
550-857	833.66.618	MODUL Q PROJECT 900, canopy direct mounting with CASAMBI control, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	452.54	407.29
550-868	833.66.619	MODUL R PROJECT 600, canopy direct mounting with CASAMBI control, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 50 W, IP 20	452.54	407.29
550-927	833.66.620	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 11.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	545.71	491.14
550-928	833.66.621	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 15.1 W, 230 V AC, 50 Hz, 3000 K, IP 20	710.27	639.24
550-981	833.66.622	ROXXANE FLY CL, battery-powered luminaire with gesture control, with lithium-ion battery, cableless magnetic with USB charging cable aluminium, black, powder-coated CRI 90, energy efficiency class F 400 lm, 2700 K, IP 20 NP	360.97	324.87
550-983	833.66.623	ROXXANE FLY CL, battery-powered luminaire with gesture control, with lithium-ion battery, cableless magnetic with USB charging cable aluminium, white, powder-coated CRI 90, energy efficiency class F 400 lm, 2700 K, IP 20 NP	360.97	324.87

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
550-984	833.66.624	ROXXANE FLY CL, battery-powered luminaire with gesture control, with lithium-ion battery, cableless magnetic with USB charging cable aluminium, red, powder-coated CRI 90, energy efficiency class F 400 lm, 2700 K, IP 20 NP	360.97	324.87
550-986	833.66.625	ROXXANE FLY CL, battery-powered luminaire with gesture control, with lithium-ion battery, cableless magnetic with USB charging cable aluminium, yellow (NEON), RAL 1026, varnished CRI 90, energy efficiency class F 400 lm, 2700 K, IP 20 NP	360.97	324.87
551-089	833.66.626	MODUL R PROJECT 1200, canopy direct mounting with CASAMBI control, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	658.24	592.42
551-218	833.66.627	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 12.9 W, 24 V DC, 4000 K, IP 20	607.42	546.68
551-219	833.66.628	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,1 W, 24 V DC, 3000 K, IP 20	764.72	688.25
551-398	833.66.629	MODUL Q PROJECT 1200, canopy direct mounting with CASAMBI control, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	658.24	592.42
551-401	833.66.630	CONVERTER capable for emergency lighting 230 V AC, 0/50/60 Hz, output 24 V DC, 96 W, IP 20	212.96	191.66
551-420	833.66.631	MODUL R PROJECT 900, canopy direct mounting with CASAMBI control, version for 230 V AC white, brilliant 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	452.54	407.29
551-481	833.66.632	ROXXANE FLY CL, wall bracket/wall suspension self-adhesive steel, white, powder-coated	18.31	16.48
551-999	833.66.633	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLs, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,9 W, 24 V DC, 3000 K, IP 20	655.82	590.24

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-001	833.66.634	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,8 W, 24 V DC, 4000 K, IP 20	655.82	590.24
552-085	833.66.636	CONVERTER switchable 230 V AC, 50 Hz, output 24 V DC, 18 W NP	85.91	77.32
552-236	833.66.639	ROXXANE FLY CL, wall bracket/wall suspension direct mounting steel, white, powder-coated NP	22.37	20.14
552-368	833.66.642	OFFICE AIR 2.0, floorstanding luminaire with presence and light sensor double-sided aluminium, chrome plated CRI 80 8.400 lm, 62.7 W, 230 V AC, 50 Hz, 3000 K, IP 20	2993.54	2694.19
552-369	833.66.643	OFFICE AIR 2.0, floorstanding luminaire with presence and light sensor double-sided aluminium, chrome plated CRI 80 8.400 lm, 62.7 W, 230 V AC, 50 Hz, 4000 K, IP 20	2993.54	2694.19
552-371	833.66.644	OFFICE AIR 2.0 POWER, floorstanding luminaire with presence and light sensor double-sided aluminium, chrome plated CRI 80 10.700 lm, 76.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	3176.25	2858.63
552-372	833.66.645	OFFICE AIR 2.0 POWER, floorstanding luminaire with presence and light sensor double-sided aluminium, chrome plated CRI 80 10.700 lm, 76.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	3176.25	2858.63
552-373	833.66.646	OFFICE AIR 2.0, floorstanding luminaire with presence and light sensor double-sided aluminium, anodised CRI 80 8.400 lm, 62.7 W, 230 V AC, 50 Hz, 3000 K, IP 20	2733.39	2460.05
552-374	833.66.647	OFFICE AIR 2.0, floorstanding luminaire with presence and light sensor double-sided aluminium, anodised CRI 80 8.400 lm, 65.7 W, 230 V AC, 50 Hz, 4000 K, IP 20	2733.39	2460.05
552-376	833.66.648	OFFICE AIR 2.0 POWER, floorstanding luminaire with presence and light sensor double-sided aluminium, anodised CRI 80 10.700 lm, 76.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	2917.31	2625.58

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-377	833.66.649	OFFICE AIR 2.0 POWER, floorstanding luminaire with presence and light sensor double-sided aluminium, anodised CRI 80 10.700 lm, 76.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	2917.31	2625.58
552-378	833.66.650	OFFICE AIR 2.0, desk luminaire for USM Haller Table with presence and light sensor double-sided aluminium, chrome plated CRI 80 8.400 lm, 85.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	2993.54	2694.19
552-379	833.66.651	OFFICE AIR 2.0, desk luminaire for USM Haller Table with presence and light sensor double-sided aluminium, chrome plated CRI 80 8.400 lm, 85.8 W, 230 V AC, 50 Hz, 3000 K, IP 20	2993.54	2694.19
552-380	833.66.652	OFFICE AIR 2.0 POWER, desk luminaire for USM Haller Table with presence and light sensor double-sided aluminium, chrome plated CRI 80 10.700 lm, 76.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	3176.25	2858.63
552-381	833.66.653	OFFICE AIR 2.0 POWER, desk luminaire for USM Haller Table with presence and light sensor double-sided aluminium, chrome plated CRI 80 10.700 lm, 76.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	3176.25	2858.63
552-492	833.66.654	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6.2 W, 24 V DC, 3000 K, IP 20	295.24	265.72
552-496	833.66.655	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6.1 W, 24 V DC, 4000 K, IP 20	295.24	265.72
552-502	833.66.656	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,2 W, 24 V DC, 3000 K, IP 20	453.75	408.38

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-504	833.66.657	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,1 W, 24 V DC, 4000 K, IP 20	453.75	408.38
552-508	833.66.658	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,2 W, 24 V DC, 3000 K, IP 20	481.58	433.42
552-510	833.66.659	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,1 W, 24 V DC, 4000 K, IP 20	481.58	433.42
552-520	833.66.660	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,2 W, 24 V DC, 3000 K, IP 20	579.59	521.63
552-522	833.66.661	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,1 W, 24 V DC, 4000 K, IP 20	579.59	521.63
552-543	833.66.666	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	757.46	681.71
552-545	833.66.667	MODUL Q PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	757.46	681.71
552-599	833.66.668	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,8 W, 24 V DC, 3000 K, IP 20	848.21	763.39

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-600	833.66.669	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLs, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,6 W, 24 V DC, 4000 K, IP 20	848.21	763.39
552-706	833.66.670	ROXXANE LEGGERA CL, charging device magnetic with power adapter black, matt 230 V AC, 50 Hz, output 24 V DC, 48 W, IP 20 NP	108.80	97.92
552-718	833.66.671	ROXXANE LEGGERA 101 CL SET, reading luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, black, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	904.96	814.46
552-719	833.66.672	ROXXANE LEGGERA 52 SET, desk luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, black, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	831.74	748.57
552-720	833.66.673	ROXXANE LEGGERA 101 CL SET, reading luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, white, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	904.96	814.46
552-721	833.66.674	ROXXANE LEGGERA 52 SET, desk luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, white, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	831.74	748.57
552-722	833.66.675	ROXXANE LEGGERA 101 CL SET, reading luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, basalt grey, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	904.96	814.46
552-723	833.66.676	ROXXANE LEGGERA 52 SET, desk luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, basalt grey, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	831.74	748.57

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-725	833.66.677	ROXXANE LEGGERA 101 CL SET, reading luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, dark bronze, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	1048.33	943.50
552-726	833.66.678	ROXXANE LEGGERA 52 SET, desk luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, dark bronze, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	968.00	871.20
552-837	833.66.679	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,1 W, 24 V DC, 4000 K, IP 20	444.07	399.66
552-838	833.66.680	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,2 W, 24 V DC, 3000 K, IP 20	601.37	541.23
552-840	833.66.681	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,1 W, 24 V DC, 4000 K, IP 20	601.37	541.23
552-848	833.66.682	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,2 W, 24 V DC, 3000 K, IP 20	728.42	655.58
552-851	833.66.683	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,1 W, 24 V DC, 4000 K, IP 20	728.42	655.58
552-917	833.66.684	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 12,9 W, 24 V DC, 4000 K, IP 20	764.72	688.25

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-918	833.66.685	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,1 W, 24 V DC, 3000 K, IP 20	793.76	714.38
552-920	833.66.686	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 12,9 W, 24 V DC, 4000 K, IP 20	793.76	714.38
552-924	833.66.687	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLs, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,1 W, 24 V DC, 3000 K, IP 20	892.98	803.68
552-926	833.66.688	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLs, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 12,9 W, 24 V DC, 4000 K, IP 20	892.98	803.68
552-956	833.66.689	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 14.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	710.27	639.24
552-958	833.66.690	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.1 W, 230 V AC, 50 Hz, 4000 K, IP 20	545.71	491.14
552-959	833.66.691	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 11,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	723.58	651.22
552-961	833.66.692	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,1 W, 230 V AC, 50 Hz, 4000 K, IP 20	723.58	651.22

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-962	833.66.693	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 11.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	703.01	632.71
552-964	833.66.694	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.1 W, 230 V AC, 50 Hz, 4000 K, IP 20	703.01	632.71
552-965	833.66.695	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 11.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	788.92	710.03
552-967	833.66.696	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.1 W, 230 V AC, 50 Hz, 4000 K, IP 20	788.92	710.03
552-968	833.66.697	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 11.0 W, 230 V AC, 50 Hz, 3000 K, IP 20	831.27	748.14
552-970	833.66.698	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10.1 W, 230 V AC, 50 Hz, 4000 K, IP 20	831.27	748.14
552-990	833.66.699	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 15,1 W, 230 V AC, 50 Hz, 3000 K, IP 20	885.72	797.15
552-992	833.66.700	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment dimmable, DALI/switchDIM, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 14,8 W, 230 V AC, 50 Hz, 4000 K, IP 20	885.72	797.15

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
552-993	833.66.701	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 15.1 W, 230 V AC, 50 Hz, 3000 K, IP 20	868.78	781.90
552-995	833.66.702	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 14.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	868.78	781.90
552-996	833.66.703	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 15.1 W, 230 V AC, 50 Hz, 3000 K, IP 20	954.69	859.22
552-998	833.66.704	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 14.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	954.69	859.22
552-999	833.66.705	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 15.1 W, 230 V AC, 50 Hz, 3000 K, IP 20	995.83	896.25
553-001	833.66.706	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 14.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	995.83	896.25
553-034	833.66.707	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	398.09	358.28
553-036	833.66.708	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment switchable, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	398.09	358.28
553-037	833.66.709	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	555.39	499.85

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
553-039	833.66.710	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	555.39	499.85
553-040	833.66.711	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	641.30	577.17
553-042	833.66.712	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	641.30	577.17
553-046	833.66.713	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	683.65	615.29
553-048	833.66.714	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with ZigBee and PDLS, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	683.65	615.29
553-249	833.66.715	MODUL Q/R PROJECT 220/280/340, suspension kit for ceiling mounting max. suspended length 2000 mm with 230 V supply cord white, brilliant	188.76	169.88
553-250	833.66.716	MODUL Q/R PROJECT 220/280/340, suspension kit for ceiling mounting max. suspended length 4000 mm with 230 V supply cord white, brilliant	217.80	196.02
553-571	833.66.717	Casambi, wall switch with wall mounting set with CASAMBI control black IP 20	301.29	271.16
553-572	833.66.718	Casambi, wall switch with wall mounting set with CASAMBI control white IP 20	301.29	271.16
553-577		COMBI CONVERTER dimmable, DALI/switchDIM 230 V AC, 50 Hz, output 24 V DC, 100 W, IP 20	278.30	250.47
553-780	833.66.719	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5.9 W, 24 V DC, 3000 K, IP 20	369.05	332.15

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
553-782	833.66.720	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 24 V DC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,8 W, 24 V DC, 4000 K, IP 20	369.05	332.15
553-783	833.66.721	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,9 W, 24 V DC, 3000 K, IP 20	527.56	474.80
553-785	833.66.722	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,8 W, 24 V DC, 4000 K, IP 20	527.56	474.80
553-786	833.66.723	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,9 W, 24 V DC, 3000 K, IP 20	555.39	499.85
553-788	833.66.724	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,8 W, 24 V DC, 4000 K, IP 20	555.39	499.85
553-792	833.66.725	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,9 W, 24 V DC, 3000 K, IP 20	654.61	589.15
553-794	833.66.726	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLS, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,8 W, 24 V DC, 4000 K, IP 20	654.61	589.15
553-812	833.66.727	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	471.90	424.71

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
553-814	833.66.728	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment switchable, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	471.90	424.71
553-815	833.66.729	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	629.20	566.28
553-819	833.66.730	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLs, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	756.25	680.63
553-821	833.66.731	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee and PDLs, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	756.25	680.63
553-823	833.66.732	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with ZigBee, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	629.20	566.28
553-824	833.66.733	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	715.11	643.60
553-826	833.66.734	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with CASAMBI control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	715.11	643.60
554-074	833.66.735	ROXXANE LEGGERA CL, smartphone holder self-supporting black, matt	48.81	43.93
554-144	833.66.747	PWM DIMMING UNIT for push button operation 24 V DC, output 24 V DC, 150 W, IP 20	130.68	117.61
554-424		WINGLET CL /ROXXANE FLY CL, charging cable length 1.5 m black NP	12.22	11.00
554-677	833.66.748	ROXXANE FLY CL, USB plug-in power supply 230 V AC, output 5 V DC, 12 W, IP 20 NP	42.35	38.12

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
554-809	833.66.749	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,9 W, 24 V DC, 3000 K, IP 20	598.95	539.06
554-811	833.66.750	MODUL Q PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 8,8 W, 24 V DC, 4000 K, IP 20	598.95	539.06
554-834	833.66.751	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,2 W, 24 V DC, 3000 K, IP 20	670.34	603.31
554-836	833.66.752	MODUL R PROJECT 280, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 9,1 W, 24 V DC, 4000 K, IP 20	670.34	603.31
554-840	833.66.753	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,8 W, 24 V DC, 3000 K, IP 20	790.13	711.12
554-842	833.66.754	MODUL Q PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,6 W, 24 V DC, 4000 K, IP 20	790.13	711.12
554-858	833.66.755	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 13,1 W, 24 V DC, 3000 K, IP 20	834.90	751.41
554-859	833.66.756	MODUL R PROJECT 340, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 12,9 W, 24 V DC, 4000 K, IP 20	834.90	751.41

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
554-866	833.66.757	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,2 W, 24 V DC, 3000 K, IP 20	523.93	471.54
554-868	833.66.758	MODUL Q PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 6,1 W, 24 V DC, 4000 K, IP 20	523.93	471.54
554-883	833.66.759	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,9 W, 24 V DC, 3000 K, IP 20	597.74	537.97
554-885	833.66.760	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 24 V DC, with forwarding voltage 24 V with mounting ring acrylic, satin-frosted CRI 80 750 lm, 5,8 W, 24 V DC, 4000 K, IP 20	597.74	537.97
554-907	833.66.761	WINGLET CL, wall luminaire, near-ground with magnetic attachment with presence and light sensor, with lithium-ion battery, cableless, double-sided with wall bracket white, matt CRI 90 170 lm, 2700 K, IP 20 NP	202.35	182.11
554-908	833.66.762	WINGLET CL, wall luminaire, near-ground with magnetic attachment with presence and light sensor, with lithium-ion battery, cableless, double-sided with wall bracket black, matt CRI 90 170 lm, 2700 K, IP 20 NP	202.35	182.11
554-909	833.66.763	WINGLET CL, charging device with power adapter white, matt 230 V AC, 50 Hz, output 5 V DC, 60 W, IP 20 NP	202.35	182.11
554-910	833.66.764	WINGLET CL, wall bracket/wall suspension self-adhesive white, matt NP	32.54	29.28
554-922	833.66.765	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with IQ control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 12,5 W, 230 V AC, 50 Hz, 2700 K, IP 20	701.80	631.62

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
554-923	833.66.766	MODUL Q 49, ceiling luminaire with surface-mounted housing, with magnetic attachment with IQ control, version for 230 V AC acrylic, satin-frosted CRI 90 1.050 lm, 11.9 W, 230 V AC, 50 Hz, 3000 K, IP 20	701.80	631.62
554-926	833.66.767	MODUL Q 64, ceiling luminaire with surface-mounted housing, with magnetic attachment with IQ control, version for 230 V AC acrylic, satin-frosted CRI 90 1.350 lm, 13.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	908.71	817.84
554-945		COMBI CONVERTER dimmable, DALI/switchDIM 230 V AC, 50 Hz, output 24 V DC, 35 W, IP 20 NP	147.62	132.86
554-964	833.66.768	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 3000 K, IP 20	700.59	630.53
554-966	833.66.769	MODUL R PROJECT 220, ceiling luminaire direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 750 lm, 7.3 W, 230 V AC, 50 Hz, 4000 K, IP 20	700.59	630.53
554-970	833.66.770	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.6 W, 230 V AC, 50 Hz, 3000 K, IP 20	625.57	563.01
554-972	833.66.771	MODUL Q PROJECT 220, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC acrylic, satin-frosted CRI 80 750 lm, 7.5 W, 230 V AC, 50 Hz, 4000 K, IP 20	625.57	563.01
554-976	833.66.772	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 15.1 W, 230 V AC, 50 Hz, 3000 K, IP 20	938.96	845.06
554-978	833.66.773	MODUL R PROJECT 340, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 14.8 W, 230 V AC, 50 Hz, 4000 K, IP 20	938.96	845.06

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
554-982	833.66.774	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 11,0 W, 230 V AC, 50 Hz, 3000 K, IP 20	774.40	696.96
554-984	833.66.775	MODUL R PROJECT 280, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,1 W, 230 V AC, 50 Hz, 4000 K, IP 20	774.40	696.96
554-988	833.66.776	MODUL Q PROJECT 280, ceiling luminaire, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,9 W, 230 V AC, 50 Hz, 3000 K, IP 20	701.80	631.62
554-990	833.66.777	MODUL Q PROJECT 280, ceiling luminaire, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.200 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20	701.80	631.62
554-994	833.66.778	MODUL Q PROJECT 340, ceiling luminaire, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16,5 W, 230 V AC, 50 Hz, 3000 K, IP 20	894.19	804.77
554-996	833.66.779	MODUL Q PROJECT 340, ceiling luminaire, surface-mounted ceiling light direct mounting, with magnetic attachment with IQ control, version for 230 V AC with mounting ring acrylic, satin-frosted CRI 80 1.800 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	894.19	804.77
555-030	833.66.780	ROXXANE LEGGERA CL WK, reading luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, bronze, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	1507.93	1357.13
555-433	833.66.781	CONVERTER switchable 230 V AC, 50 Hz, output 24 V DC, 70 W, IP 20	152.46	137.21

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-517	833.66.782	CUBIC 36, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 630 lm, 7.1 W, 24 V DC, 2700 K, IP 20	242.00	217.80
555-518	833.66.783	CUBIC 36, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 630 lm, 6.8 W, 24 V DC, 3000 K, IP 20	242.00	217.80
555-519	833.66.784	CUBIC 36, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 630 lm, 6.5 W, 24 V DC, 4000 K, IP 20	242.00	217.80
555-660	833.66.785	MODUL L 196 POWER, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 10.050 lm, 92,0 W, 24 V DC, 3000 K, IP 20	1839.20	1655.28
555-661	833.66.786	MODUL L 196 POWER, suspended luminaire suspended mounting version for 24 V DC double-sided, max. suspended length 1500 mm with suspension kit aluminium, anodised CRI 80 10.050 lm, 92,0 W, 24 V DC, 4000 K, IP 20	1839.20	1655.28
555-679	833.66.787	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, grey dawn CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1867.03	1680.33
555-680	833.66.788	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, grey dawn CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1867.03	1680.33

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-681	833.66.789	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, grey dawn CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1867.03	1680.33
555-682	833.66.790	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, grey dawn CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2296.58	2066.92
555-683	833.66.791	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, grey dawn CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2296.58	2066.92
555-684	833.66.792	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, grey dawn CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2296.58	2066.92
555-685	833.66.793	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, white CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1867.03	1680.33
555-686	833.66.794	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, white CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1867.03	1680.33

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-687	833.66.795	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, white CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1867.03	1680.33
555-688	833.66.796	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, white CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2296.58	2066.92
555-689	833.66.797	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, white CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2296.58	2066.92
555-690	833.66.798	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, white CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2296.58	2066.92
555-691	833.66.799	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, grey dawn CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1867.03	1680.33
555-692	833.66.800	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, grey dawn CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1867.03	1680.33

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-693	833.66.801	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, grey dawn CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1867.03	1680.33
555-694	833.66.802	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, grey dawn CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2296.58	2066.92
555-695	833.66.803	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, grey dawn CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2296.58	2066.92
555-696	833.66.804	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, grey dawn CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2296.58	2066.92
555-697	833.66.805	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, white CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1867.03	1680.33
555-698	833.66.806	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, white CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1867.03	1680.33

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-699	833.66.807	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, white CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1867.03	1680.33
555-700	833.66.808	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, white CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2296.58	2066.92
555-701	833.66.809	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, white CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2296.58	2066.92
555-702	833.66.810	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, white CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2296.58	2066.92
555-711	833.66.811	LIGHTING PAD Q 600/900/1200, suspension kit for ceiling mounting max. suspended length 2000 mm with 230 V supply cord stainless steel	128.26	115.43
555-712	833.66.812	LIGHTING PAD Q 600/900/1200, suspension kit for ceiling mounting max. suspended length 4000 mm with 230 V supply cord stainless steel	141.57	127.41
555-713	833.66.813	LIGHTING PAD R 600/900/1200, suspension kit for ceiling mounting max. suspended length 2000 mm with 230 V supply cord stainless steel	100.43	90.39
555-714	833.66.814	LIGHTING PAD R 600/900/1200, suspension kit for ceiling mounting max. suspended length 4000 mm with 230 V supply cord stainless steel	110.11	99.10
555-716	833.66.815	MODUL Q/R PROJECT 220/280/340, suspension kit for ceiling mounting with forwarding voltage 24 V, max. suspended length 2000 mm with 24 V supply cord white, brilliant	188.76	169.88

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-718	833.66.816	MODUL Q/R PROJECT 220/280/340, suspension kit for ceiling mounting with forwarding voltage 24 V, max. suspended length 4000 mm with 24 V supply cord white, brilliant	217.80	196.02
555-719	833.66.817	MODUL Q/R PROJECT 220/280/340, suspension kit for ceiling mounting max. suspended length 2000 mm with 24 V supply cord white, brilliant	188.76	169.88
555-721	833.66.818	MODUL Q/R PROJECT 220/280/340, suspension kit for ceiling mounting max. suspended length 4000 mm with 24 V supply cord white, brilliant	217.80	196.02
555-727	833.66.819	WINGLET CL SET 3, wall luminaire, near-ground with magnetic attachment with presence and light sensor, with lithium-ion battery, cableless, double-sided with wall bracket, with Basket Charger black, matt CRI 90 170 lm, 2700 K, IP 20 NP	690.41	621.37
555-728	833.66.820	WINGLET CL SET 3, wall luminaire, near-ground with magnetic attachment with presence and light sensor, with lithium-ion battery, cableless, double-sided with wall bracket, with Basket Charger white, matt CRI 90 170 lm, 2700 K, IP 20 NP	690.41	621.37
555-780	833.66.821	CUBIC 49, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 880 lm, 10.3 W, 24 V DC, 2700 K, IP 20	327.91	295.12
555-781	833.66.822	CUBIC 49, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 880 lm, 9.8 W, 24 V DC, 3000 K, IP 20	327.91	295.12
555-782	833.66.823	CUBIC 49, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 880 lm, 9.3 W, 24 V DC, 4000 K, IP 20	327.91	295.12
555-789	833.66.824	CUBIC 64, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 1.100 lm, 11.5 W, 24 V DC, 2700 K, IP 20	493.68	444.31

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
555-790	833.66.825	CUBIC 64, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 1.100 lm, 10.9 W, 24 V DC, 3000 K, IP 20	493.68	444.31
555-791	833.66.826	CUBIC 64, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 1.100 lm, 10.5 W, 24 V DC, 4000 K, IP 20	493.68	444.31
555-795	833.66.827	CUBIC 9, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 160 lm, 2.9 W, 24 V DC, 2700 K, IP 20	136.73	123.06
555-796	833.66.828	CUBIC 9, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 160 lm, 2.7 W, 24 V DC, 3000 K, IP 20	136.73	123.06
555-797	833.66.829	CUBIC 9, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 160 lm, 2.6 W, 24 V DC, 4000 K, IP 20	136.73	123.06
555-833	833.66.830	COMBI CONVERTER dimmable, DALI/switchDIM 230 V AC, 50 Hz, output 24 V DC, 150 W, IP 20	317.02	285.32
555-916	833.66.831	COMBI CONVERTER with phase control dimmer 230 V AC, 50 Hz, output 24 V DC, 75 W, IP 20	192.39	173.15
556-384	833.66.832	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, far mountain CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76
556-385	833.66.833	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, nightfall CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-386	833.66.834	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, soft moss CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76
556-387	833.66.835	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, vineyard CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76
556-388	833.66.836	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, yellow field CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76
556-643	833.66.837	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, far mountain CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-644	833.66.838	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, far mountain CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-645	833.66.839	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, far mountain CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-646	833.66.840	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, far mountain CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-647	833.66.841	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, far mountain CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-648	833.66.842	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, far mountain CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-649	833.66.843	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, nightfall CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-650	833.66.844	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, nightfall CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-651	833.66.845	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, nightfall CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-652	833.66.846	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, nightfall CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-653	833.66.847	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, nightfall CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-654	833.66.848	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, nightfall CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-655	833.66.849	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, soft moss CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-656	833.66.850	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, soft moss CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-657	833.66.851	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, soft moss CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-658	833.66.852	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, soft moss CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-659	833.66.853	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, soft moss CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-660	833.66.854	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, soft moss CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-661	833.66.855	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, vineyard CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-662	833.66.856	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, vineyard CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-663	833.66.857	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, vineyard CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-664	833.66.858	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, vineyard CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-665	833.66.859	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, vineyard CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-666	833.66.860	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, vineyard CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-667	833.66.861	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, yellow field CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-668	833.66.862	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, yellow field CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-669	833.66.863	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, yellow field CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-670	833.66.864	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, yellow field CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-671	833.66.865	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, yellow field CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-672	833.66.866	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, yellow field CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-673	833.66.867	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, far mountain CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-674	833.66.868	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, far mountain CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-675	833.66.869	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, far mountain CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-676	833.66.870	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, far mountain CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-677	833.66.871	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, far mountain CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-678	833.66.872	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, nightfall CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-679	833.66.873	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, nightfall CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-680	833.66.874	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, nightfall CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-681	833.66.875	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, nightfall CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-682	833.66.876	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, nightfall CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-683	833.66.877	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, soft moss CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-684	833.66.878	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, soft moss CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-685	833.66.879	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, soft moss CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-686	833.66.880	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, soft moss CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-687	833.66.881	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, soft moss CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-688	833.66.882	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, vineyard CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76
556-689	833.66.883	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, vineyard CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-690	833.66.884	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, vineyard CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-691	833.66.885	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, vineyard CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-692	833.66.886	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, vineyard CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
556-693	833.66.887	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, yellow field CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
556-694	833.66.888	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, yellow field CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
556-695	833.66.889	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, yellow field CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
556-696	833.66.890	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, yellow field CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
556-697	833.66.891	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, yellow field CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
557-469	833.67.020	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, far mountain CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-470	833.67.021	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, far mountain CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-471	833.67.022	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, far mountain CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-472	833.67.023	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, far mountain CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-473	833.67.024	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, far mountain CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-474	833.67.025	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, far mountain CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-475	833.67.026	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, grey dawn CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1579.05	1421.15
557-476	833.67.027	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, grey dawn CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2009.81	1808.83

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-477	833.67.028	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, grey dawn CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1579.05	1421.15
557-478	833.66.892	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, grey dawn CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2009.81	1808.83
557-479	833.66.893	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, grey dawn CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1579.05	1421.15
557-480	833.67.029	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, grey dawn CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2009.81	1808.83
557-481	833.67.030	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, nightfall CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
557-482	833.66.894	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, nightfall CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-483	833.67.031	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, nightfall CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-484	833.67.032	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, nightfall CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-485	833.67.033	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, nightfall CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-486	833.67.034	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, nightfall CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-487	833.67.035	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, soft moss CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-488	833.67.036	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, soft moss CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-489	833.67.037	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, soft moss CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
557-490	833.66.895	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided, indirect light 2200-5700 K without suspension kit fleece, soft moss CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-491	833.67.038	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, soft moss CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-492	833.67.039	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, soft moss CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-493	833.67.040	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, vineyard CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-494	833.67.041	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, vineyard CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-495	833.67.042	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, vineyard CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
557-496	833.66.896	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, vineyard CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-497	833.67.043	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, vineyard CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-498	833.67.044	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, vineyard CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-499	833.67.045	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, white CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1579.05	1421.15
557-501	833.67.046	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, white CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1579.05	1421.15

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-502	833.66.897	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, white CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2009.81	1808.83
557-503	833.67.047	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, white CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1579.05	1421.15
557-504	833.67.048	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, white CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2009.81	1808.83
557-505	833.67.049	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, yellow field CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-506	833.67.050	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, yellow field CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
557-507	833.67.051	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, yellow field CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-508	833.67.052	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, yellow field CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-509	833.67.053	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, yellow field CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-510	833.67.054	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, yellow field CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-511	833.67.055	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, far mountain CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-512	833.67.056	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, far mountain CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-513	833.66.898	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, far mountain CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-514	833.66.899	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, far mountain CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-515	833.67.057	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, far mountain CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-516	833.67.058	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, far mountain CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-517	833.67.059	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, grey dawn CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1579.05	1421.15
557-518	833.66.900	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, grey dawn CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2009.81	1808.83
557-519	833.66.901	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, grey dawn CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1579.05	1421.15

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-520	833.66.902	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, grey dawn CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2009.81	1808.83
557-521	833.67.060	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, grey dawn CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1579.05	1421.15
557-522	833.66.903	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, grey dawn CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2009.81	1808.83
557-523	833.67.061	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, nightfall CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-524	833.66.904	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, nightfall CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-525	833.66.905	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, nightfall CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-526	833.66.906	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, nightfall CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-527	833.67.062	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, nightfall CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-528	833.67.063	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, nightfall CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-529	833.66.907	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, soft moss CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
557-530	833.66.908	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, soft moss CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-531	833.67.064	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, soft moss CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-532	833.66.909	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, soft moss CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-533	833.67.065	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, soft moss CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-534	833.67.066	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, soft moss CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-535	833.67.067	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, vineyard CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-536	833.67.068	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, vineyard CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-537	833.66.910	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, vineyard CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-538	833.66.911	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, vineyard CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
557-539	833.67.069	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, vineyard CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-540	833.67.070	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, vineyard CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-541	833.66.912	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, white CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1579.05	1421.15
557-542	833.66.913	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, white CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2009.81	1808.83
557-543	833.66.914	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, white CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1579.05	1421.15

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-544	833.66.915	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, white CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2009.81	1808.83
557-545	833.66.916	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, white CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1579.05	1421.15
557-546	833.66.917	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, white CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2009.81	1808.83
557-547	833.67.071	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, yellow field CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75
557-548	833.66.918	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, yellow field CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
557-549	833.66.919	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, yellow field CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-550	833.67.072	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, yellow field CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
557-551	833.66.920	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, yellow field CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
557-552	833.67.073	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, yellow field CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
557-577	833.67.074	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, white CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2009.81	1808.83
557-649	833.66.921	Q ONE AUFBAU, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	260.15	234.14
557-650	833.66.922	Q ONE AUFBAU, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring black, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	260.15	234.14
557-651	833.66.923	Q ONE AUFBAU, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring black, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	260.15	234.14

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-652	833.66.924	Q ONE AUFBAU, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	260.15	234.14
557-653	833.66.925	Q ONE AUFBAU, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring white, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	260.15	234.14
557-654	833.66.926	Q ONE AUFBAU, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring white, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	260.15	234.14
557-655	833.66.927	Q ONE AUFBAU, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	324.28	291.85
557-656	833.66.928	Q ONE AUFBAU, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring black, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	324.28	291.85
557-657	833.66.929	Q ONE AUFBAU, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring black, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	324.28	291.85
557-658	833.66.930	Q ONE AUFBAU, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	324.28	291.85

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-659	833.66.931	Q ONE AUFBAU, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring white, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	324.28	291.85
557-660	833.66.932	Q ONE AUFBAU, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring white, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	324.28	291.85
557-685	833.66.933	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring black, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	404.14	363.73
557-686	833.66.934	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring black, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	404.14	363.73
557-687	833.66.935	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	404.14	363.73
557-688	833.66.936	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring white, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	404.14	363.73
557-689	833.66.937	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring white, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	404.14	363.73

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-690	833.66.938	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	404.14	363.73
557-691	833.66.939	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring black, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	404.14	363.73
557-692	833.66.940	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring black, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	404.14	363.73
557-693	833.66.941	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	404.14	363.73
557-694	833.66.942	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring white, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	404.14	363.73
557-695	833.66.943	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring white, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	404.14	363.73

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-696	833.66.944	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	404.14	363.73
557-725	833.67.500	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	543.29	488.96
557-726	833.67.501	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	543.29	488.96
557-727	833.67.502	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	543.29	488.96
557-728	833.67.503	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	543.29	488.96
557-729	833.67.504	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	543.29	488.96

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-730	833.67.505	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	543.29	488.96
557-731	833.67.506	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	543.29	488.96
557-732	833.67.507	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	543.29	488.96
557-733	833.67.508	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	543.29	488.96
557-734	833.67.509	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 600 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	543.29	488.96
557-735	833.67.510	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 660 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	543.29	488.96

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-736	833.67.511	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	543.29	488.96
557-794	833.66.945	MODUL Q 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated CRI 90 750 lm, 9,9 W, 230 V AC, 50 Hz, 2700 K, IP 20	436.81	393.13
557-795	833.66.946	MODUL Q 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated CRI 90 750 lm, 9,6 W, 230 V AC, 50 Hz, 3000 K, IP 20	436.81	393.13
557-796	833.66.947	MODUL Q 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated CRI 90 750 lm, 9,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	436.81	393.13
557-797	833.66.948	MODUL Q 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated CRI 90 750 lm, 9,9 W, 230 V AC, 50 Hz, 2700 K, IP 20	436.81	393.13
557-798	833.66.949	MODUL Q 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated CRI 90 750 lm, 9,6 W, 230 V AC, 50 Hz, 3000 K, IP 20	436.81	393.13
557-799	833.66.950	MODUL Q 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated CRI 90 750 lm, 9,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	436.81	393.13
557-800	833.66.951	CUBIC 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated CRI 90 630 lm, 9,9 W, 230 V AC, 50 Hz, 2700 K, IP 20	436.81	393.13
557-801	833.66.952	CUBIC 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated CRI 90 630 lm, 9,6 W, 230 V AC, 50 Hz, 3000 K, IP 20	436.81	393.13

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-802	833.66.953	CUBIC 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated CRI 90 630 lm, 9,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	436.81	393.13
557-803	833.66.954	CUBIC 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated CRI 90 630 lm, 9,9 W, 230 V AC, 50 Hz, 2700 K, IP 20	436.81	393.13
557-804	833.66.955	CUBIC 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated CRI 90 630 lm, 9,6 W, 230 V AC, 50 Hz, 3000 K, IP 20	436.81	393.13
557-805	833.66.956	CUBIC 36 FRAME, surface-mounted ceiling light direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated CRI 90 630 lm, 9,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	436.81	393.13
557-806	833.66.957	FRAME 36, surface-mounted housing direct mounting with phase control dimmer, version for 230 V AC aluminium, black, matt, powder-coated 230 V AC, 50 Hz, output 24 V DC, 15 W, IP 20	196.02	176.42
557-807	833.66.958	FRAME 36, surface-mounted housing direct mounting with phase control dimmer, version for 230 V AC aluminium, white, matt, powder-coated 230 V AC, 50 Hz, output 24 V DC, 15 W, IP 20	196.02	176.42
557-814	833.66.959	Q ONE, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring, with external converter black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	260.15	234.14
557-815	833.66.960	Q ONE, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring, with external converter black, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	260.15	234.14
557-816	833.66.961	Q ONE, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring, with external converter black, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	260.15	234.14

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-817	833.66.962	Q ONE, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring, with external converter white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	260.15	234.14
557-818	833.66.963	Q ONE, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring, with external converter white, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	260.15	234.14
557-819	833.66.964	Q ONE, wallwasher direct mounting with phase control dimmer, version for 230 V AC with mounting ring, with external converter white, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	260.15	234.14
557-820	833.66.965	Q ONE, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring, with external converter black, matt CRI 90 700 lm, 10,3 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	324.28	291.85
557-821	833.66.966	Q ONE, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring, with external converter black, matt CRI 90 730 lm, 10,3 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	324.28	291.85
557-822	833.66.967	Q ONE, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring, with external converter black, matt CRI 90 780 lm, 10,3 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	324.28	291.85
557-823	833.66.968	Q ONE, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring, with external converter white, matt CRI 90 700 lm, 10,3 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	324.28	291.85

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-824	833.66.969	Q ONE, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring, with external converter white, matt CRI 90 730 lm, 10,3 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	324.28	291.85
557-825	833.66.970	Q ONE, wallwasher direct mounting dimmable, DALI, version for 230 V AC with mounting ring, with external converter white, matt CRI 90 780 lm, 10,3 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	324.28	291.85
557-830	833.66.971	Q FOUR 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring, with external converter black, matt CRI 90 750 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	331.54	298.39
557-831	833.66.972	Q FOUR 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring, with external converter black, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	331.54	298.39
557-832	833.66.973	Q FOUR 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring, with external converter black, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	331.54	298.39
557-833	833.66.974	Q FOUR 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring, with external converter white, matt CRI 90 750 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	331.54	298.39
557-834	833.66.975	Q FOUR 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring, with external converter white, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	331.54	298.39

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-835	833.66.976	Q FOUR 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring, with external converter white, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	331.54	298.39
557-836	833.66.977	Q FOUR 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring, with external converter black, matt CRI 90 750 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	331.54	298.39
557-837	833.66.978	Q FOUR 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring, with external converter black, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	331.54	298.39
557-838	833.66.979	Q FOUR 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring, with external converter black, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	331.54	298.39
557-839	833.66.980	Q FOUR 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring, with external converter white, matt CRI 90 750 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	331.54	298.39
557-840	833.66.981	Q FOUR 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring, with external converter white, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	331.54	298.39

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-841	833.66.982	Q FOUR 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring, with external converter white, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	331.54	298.39
557-842	833.66.983	Q FOUR 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring, with external converter black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	388.41	349.57
557-843	833.66.984	Q FOUR 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring, with external converter black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	388.41	349.57
557-844	833.66.985	Q FOUR 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring, with external converter black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	388.41	349.57
557-845	833.66.986	Q FOUR 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring, with external converter white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	388.41	349.57
557-846	833.66.987	Q FOUR 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring, with external converter white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	388.41	349.57

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-847	833.66.988	Q FOUR 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle with mounting ring, with external converter white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	388.41	349.57
557-848	833.66.989	Q FOUR 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring, with external converter black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	388.41	349.57
557-849	833.66.990	Q FOUR 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring, with external converter black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	388.41	349.57
557-850	833.66.991	Q FOUR 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring, with external converter black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	388.41	349.57
557-851	833.66.992	Q FOUR 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring, with external converter white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	388.41	349.57
557-852	833.66.993	Q FOUR 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring, with external converter white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	388.41	349.57

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-853	833.66.994	Q FOUR 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle with mounting ring, with external converter white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	388.41	349.57
557-862	833.66.995	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring black, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	340.01	306.01
557-863	833.66.996	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring black, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	340.01	306.01
557-864	833.66.997	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring black, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	340.01	306.01
557-865	833.66.998	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring white, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	340.01	306.01
557-866	833.66.999	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring white, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	340.01	306.01

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-867	833.67.000	Q FOUR AUFBAU 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle with mounting ring white, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	340.01	306.01
557-868	833.67.001	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring black, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	340.01	306.01
557-869	833.67.002	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring black, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	340.01	306.01
557-870	833.67.003	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring black, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	340.01	306.01
557-871	833.67.004	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring white, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	340.01	306.01
557-872	833.67.005	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring white, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	340.01	306.01

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-873	833.67.006	Q FOUR AUFBAU 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle with mounting ring white, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	340.01	306.01
557-874	833.67.512	Q FOUR TT 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	430.76	387.68
557-876	833.67.513	Q FOUR TT 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	430.76	387.68
557-878	833.67.514	Q FOUR TT 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	430.76	387.68
557-879	833.67.515	Q FOUR TT 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	430.76	387.68
557-881	833.67.516	Q FOUR TT 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	430.76	387.68

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-882	833.67.517	Q FOUR TT 40°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	430.76	387.68
557-883	833.67.518	Q FOUR TT 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	430.76	387.68
557-884	833.67.519	Q FOUR TT 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	430.76	387.68
557-885	833.67.520	Q FOUR TT 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	430.76	387.68
557-886	833.67.521	Q FOUR TT 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	430.76	387.68
557-887	833.67.522	Q FOUR TT 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	430.76	387.68

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-888	833.67.523	Q FOUR TT 80°, ceiling spotlight direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	430.76	387.68
557-889	833.67.524	Q FOUR TT 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	516.67	465.00
557-890	833.67.525	Q FOUR TT 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	516.67	465.00
557-891	833.67.526	Q FOUR TT 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	516.67	465.00
557-892	833.67.527	Q FOUR TT 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	516.67	465.00
557-893	833.67.528	Q FOUR TT 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	516.67	465.00

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-894	833.67.529	Q FOUR TT 40°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	516.67	465.00
557-895	833.67.530	Q FOUR TT 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	516.67	465.00
557-896	833.67.531	Q FOUR TT 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	516.67	465.00
557-897	833.67.532	Q FOUR TT 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	516.67	465.00
557-898	833.67.533	Q FOUR TT 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	516.67	465.00
557-899	833.67.534	Q FOUR TT 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	516.67	465.00

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-900	833.67.535	Q FOUR TT 80°, ceiling spotlight direct mounting dimmable, DALI, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring, with external converter white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	516.67	465.00
557-909	833.67.536	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	453.75	408.38
557-910	833.67.537	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	453.75	408.38
557-911	833.67.538	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	453.75	408.38
557-912	833.67.539	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	453.75	408.38
557-913	833.67.540	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	453.75	408.38

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-914	833.67.541	Q FOUR TT AUFBAU 40°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 40° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	453.75	408.38
557-915	833.67.542	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	453.75	408.38
557-916	833.67.543	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	453.75	408.38
557-917	833.67.544	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring black, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	453.75	408.38
557-918	833.67.545	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 600 lm, 11,2 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	453.75	408.38
557-919	833.67.546	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 660 lm, 11,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	453.75	408.38

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
557-920	833.67.547	Q FOUR TT AUFBAU 80°, surface-mounted ceiling spot direct mounting with phase control dimmer, version for 230 V AC 80° beam angle, rotatable and tiltable with mounting ring white, matt CRI 90 700 lm, 11,2 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	453.75	408.38
558-017	833.67.007	LIGHTING PAD Q/R, cover white, brilliant	52.03	46.83
558-082	833.67.008	COMBI CONVERTER dimmable, DALI/switchDIM 230 V AC, 50-60 Hz, output 24 V DC, 60 W NP	158.51	142.66
558-145	833.67.075	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, white, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	500.27	450.25
558-146	833.67.076	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, black, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	562.30	506.07
558-147	833.67.077	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, silver, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	562.30	506.07
558-148	833.67.078	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, dark bronze, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	562.30	506.07
558-149	833.67.079	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, white, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	500.27	450.25

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-150	833.67.080	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, black, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	562.30	506.07
558-151	833.67.081	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, silver, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	562.30	506.07
558-152	833.67.082	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, dark bronze, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	562.30	506.07
558-153	833.67.083	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, white, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	500.27	450.25
558-154	833.67.084	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, black, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	562.30	506.07
558-155	833.67.085	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, silver, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	562.30	506.07
558-156	833.67.086	ROXXANE HOME, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, dark bronze, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	562.30	506.07

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-169	833.67.087	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, white, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	841.92	757.73
558-170	833.67.088	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, black, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	841.92	757.73
558-171	833.67.089	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, silver, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	841.92	757.73
558-172	833.67.090	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, dark bronze, matt, powder-coated CRI 90 900 lm, 10,5 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	841.92	757.73
558-173	833.67.091	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, white, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	841.92	757.73
558-174	833.67.092	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, black, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	841.92	757.73
558-175	833.67.093	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, silver, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	841.92	757.73

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-176	833.67.094	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, dark bronze, matt, powder-coated CRI 90 900 lm, 10,2 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	841.92	757.73
558-177	833.67.095	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, white, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	841.92	757.73
558-178	833.67.096	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, black, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	841.92	757.73
558-179	833.67.097	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, silver, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	841.92	757.73
558-180	833.67.098	ROXXANE HOME, reading luminaire with gesture control tiltable with baseplate, with converter aluminium, dark bronze, matt, powder-coated CRI 90 900 lm, 9,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	841.92	757.73
558-184	833.67.099	ROXXANE HOME, baseplate steel, white, matt, powder-coated NP	75.24	67.71
558-185	833.67.100	ROXXANE HOME, baseplate steel, black, matt, powder-coated NP	86.43	77.79
558-186	833.67.101	ROXXANE HOME, baseplate steel, silver, matt, powder-coated NP	86.43	77.79
558-187	833.67.102	ROXXANE HOME, baseplate steel, dark bronze, matt, powder-coated NP	86.43	77.79
558-188	833.67.103	ROXXANE OFFICE, baseplate steel, white, matt, powder-coated NP	102.69	92.42
558-189	833.67.104	ROXXANE OFFICE, baseplate steel, black, matt, powder-coated NP	102.69	92.42
558-190	833.67.105	ROXXANE OFFICE, baseplate steel, silver, matt, powder-coated NP	102.69	92.42

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-191	833.67.106	ROXXANE OFFICE, baseplate steel, dark bronze, matt, powder-coated NP	102.69	92.42
558-192	833.67.107	ROXXANE OFFICE, baseplate steel, red (NEON) RAL 3026, matt, powder-coated NP	124.05	111.64
558-198	833.67.108	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, white, matt, powder-coated CRI 90 1.500 lm, 15,9 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	742.27	668.05
558-199	833.67.109	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, black, matt, powder-coated CRI 90 1.500 lm, 15,9 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	742.27	668.05
558-200	833.67.110	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, silver, matt, powder-coated CRI 90 1.500 lm, 15,9 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	742.27	668.05
558-201	833.67.111	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, dark bronze, matt, powder-coated CRI 90 1.500 lm, 15,9 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	742.27	668.05
558-202	833.67.112	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, red (NEON) RAL 3026, matt, powder-coated CRI 90 1.500 lm, 15,9 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	901.91	811.72
558-203	833.67.113	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, white, matt, powder-coated CRI 90 1.500 lm, 15,5 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	742.27	668.05

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-204	833.67.114	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, black, matt, powder-coated CRI 90 1.500 lm, 15,5 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	742.27	668.05
558-205	833.67.115	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, silver, matt, powder-coated CRI 90 1.500 lm, 15,5 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	742.27	668.05
558-206	833.67.116	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, dark bronze, matt, powder-coated CRI 90 1.500 lm, 15,5 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	742.27	668.05
558-207	833.67.117	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, red (NEON) RAL 3026, matt, powder-coated CRI 90 1.500 lm, 15,5 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	901.94	811.72
558-208	833.67.118	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, white, matt, powder-coated CRI 90 1.500 lm, 14,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	742.27	668.05
558-209	833.67.119	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, black, matt, powder-coated CRI 90 1.500 lm, 14,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	742.27	668.05
558-210	833.67.120	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, silver, matt, powder-coated CRI 90 1.500 lm, 14,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	742.27	668.05

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-211	833.67.121	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, dark bronze, matt, powder-coated CRI 90 1.500 lm, 14,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	742.27	668.05
558-212	833.67.122	ROXXANE OFFICE, desk luminaire with gesture control tiltable without mounting accessories, with converter aluminium, red (NEON) RAL 3026, matt, powder-coated CRI 90 1.500 lm, 14,7 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	901.91	811.72
558-359	833.67.009	CUBIC 9 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 160 lm 2.7 W 24 V DC 3000 K IP 44	173.03	155.73
558-360	833.67.010	CUBIC 36 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 630 lm 6.8 W 24 V DC 3000 K IP 44	340.01	306.01
558-361	833.67.011	CUBIC 49 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 880 lm 9.8 W 24 V DC 3000 K IP 44	371.47	334.32
558-362	833.67.012	CUBIC 64 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 1 100 lm 10.9 W 24 V DC 3000 K IP 44	546.92	492.23
558-502	833.67.013	CUBIC 9 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 160 lm 2.9 W 24 V DC 2700 K IP 44	173.03	155.73
558-503	833.67.014	CUBIC 9 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 160 lm 2.6 W 24 V DC 4000 K IP 44	173.03	155.73

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
558-504	833.67.015	CUBIC 36 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 630 lm, 7.1 W, 24 V DC, 2700 K, IP 44	340.01	306.01
558-505	833.67.016	CUBIC 36 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 630 lm, 6.5 W, 24 V DC, 4000 K, IP 44	340.01	306.01
558-506	833.67.017	CUBIC 49 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 880 lm, 10.3 W, 24 V DC, 2700 K, IP 44	371.47	334.32
558-507	833.67.123	CUBIC 49 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 880 lm, 9.3 W, 24 V DC, 4000 K, IP 44	371.47	334.32
558-508	833.67.018	CUBIC 64 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 1 100 lm, 11.5 W, 24 V DC, 2700 K, IP 44	546.92	492.23
558-509	833.67.019	CUBIC 64 AQUA, ceiling luminaire with magnetic attachment version for 24 V DC without mounting accessories acrylic, satin-frosted CRI 90 1 100 lm, 10.5 W, 24 V DC, 4000 K, IP 44	546.92	492.23
559-023	833.66.000	ROXXANE LEGGERA 101 CL SET, reading luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, ruby red, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	904.96	814.46
561-457		ROXXANE LEGGERA CL, replacement battery	159.72	143.75
560-180	833.67.572	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC with recessed ceiling frame, with external converter black, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	252.89	227.60

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-181	833.67.573	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC with recessed ceiling frame, with external converter black, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	252.89	227.60
560-182	833.67.574	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC with recessed ceiling frame, with external converter black, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	252.89	227.60
560-183	833.67.575	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC with recessed ceiling frame, with external converter white, matt CRI 90 700 lm, 10,8 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	252.89	227.60
560-184	833.67.576	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC with recessed ceiling frame, with external converter white, matt CRI 90 730 lm, 10,8 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	252.89	227.60
560-185	833.67.577	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC with recessed ceiling frame, with external converter white, matt CRI 90 780 lm, 10,8 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	252.89	227.60
560-186	833.67.578	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC with recessed ceiling frame, with external converter black, matt CRI 90 700 lm, 10,3 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	302.50	272.25

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-187	833.67.579	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC with recessed ceiling frame, with external converter black, matt CRI 90 730 lm, 10,3 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	302.50	272.25
560-188	833.67.580	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC with recessed ceiling frame, with external converter black, matt CRI 90 780 lm, 10,3 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	302.50	272.25
560-189	833.67.581	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC with recessed ceiling frame, with external converter white, matt CRI 90 700 lm, 10,3 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	302.50	272.25
560-190	833.67.582	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC with recessed ceiling frame, with external converter white, matt CRI 90 730 lm, 10,3 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	302.50	272.25
560-193	833.67.583	Q ONE IN, recessed wallwasher cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC with recessed ceiling frame, with external converter white, matt CRI 90 780 lm, 10,3 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	302.50	272.25
560-194	833.67.548	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	317.02	285.32

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-195	833.67.549	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	317.02	285.32
560-196	833.67.550	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	317.02	285.32
560-197	833.67.551	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	317.02	285.32
560-198	833.67.552	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	317.02	285.32
560-199	833.67.553	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	317.02	285.32

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-200	833.67.554	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	317.02	285.32
560-201	833.67.555	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	317.02	285.32
560-202	833.67.556	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	317.02	285.32
560-203	833.67.557	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 730 lm, 14,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	317.02	285.32
560-204	833.67.558	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 800 lm, 14,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	317.02	285.32

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-205	833.67.559	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm with phase control dimmer, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 850 lm, 14,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	317.02	285.32
560-206	833.67.560	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	382.36	344.12
560-207	833.67.561	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	382.36	344.12
560-208	833.67.562	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	382.36	344.12
560-209	833.67.563	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	382.36	344.12
560-211	833.67.565	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	382.36	344.12

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-212	833.67.566	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	382.36	344.12
560-213	833.67.567	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	382.36	344.12
560-214	833.67.568	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	382.36	344.12
560-215	833.67.569	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	382.36	344.12
560-216	833.67.570	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	382.36	344.12
560-218	833.67.564	Q FOUR IN 40°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 40° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	382.36	344.12

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-219	833.67.571	Q FOUR IN 80°, recessed ceiling spot cavity mounting, mounting depth in cavity 50 mm dimmable, DALI, version for 230 V AC 80° beam angle with recessed ceiling frame, with external converter black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	382.36	344.12
560-275	833.76.316	Loox 5 3042, LED stripe self-adhesive cut length 50 mm, 4,8 W/m 440 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 2 200 lm 24.0 W 24 V DC 2700 K IP 20	170.69	153.63
560-276	833.76.317	Loox 5 3042, LED stripe self-adhesive cut length 50 mm, 4,8 W/m 465 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 2 325 lm 24.0 W 24 V DC 3000 K IP 20	170.69	153.63
560-277	833.76.318	Loox 5 3042, LED stripe self-adhesive cut length 50 mm, 4,8 W/m 490 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 2 450 lm 24.0 W 24 V DC 4000 K IP 20	170.69	153.63
560-278	833.76.319	Loox 5 3042, LED stripe self-adhesive cut length 50 mm, 4,8 W/m 495 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 2 475 lm 24.0 W 24 V DC 5000 K IP 20	170.69	153.63
560-279	833.76.334	Loox 5 3045, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 920 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 4 600 lm 48.0 W 24 V DC 2700 K IP 20	222.31	200.08
560-280	833.76.335	Loox 5 3045, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 970 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 4 850 lm 48.0 W 24 V DC 3000 K IP 20	222.31	200.08

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-281	833.76.336	Loox 5 3045, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 1000 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 5.000 lm 48.0 W 24 V DC 4000 K IP 20	222.31	200.08
560-282	833.76.337	Loox 5 3045, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 1040 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 5.200 lm 48.0 W 24 V DC 5000 K IP 20	222.31	200.08
560-283	833.76.352	Loox 5 3048, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1270 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class G 6.350 lm 72.0 W 24 V DC 2700 K IP 20	255.30	229.77
560-284	833.76.353	Loox 5 3048, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1305 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class G 6.525 lm 72.0 W 24 V DC 3000 K IP 20	255.30	229.77
560-285	833.76.354	Loox 5 3048, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1340 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 6.700 lm 72.0 W 24 V DC 4000 K IP 20	255.30	229.77
560-286	833.76.355	Loox 5 3048, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1430 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 7.150 lm 72.0 W 24 V DC 5000 K IP 20	255.30	229.77
560-287	833.76.352	Loox 5 3050, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 945 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class G 4.725 lm 48.0 W 24 V DC 2700 K IP 20	261.05	234.94

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-288	833.76.363	Loox 5 3050, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 1030 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 5.150 lm 48.0 W 24 V DC 3000 K IP 20	261.05	234.94
560-289	833.76.364	Loox 5 3050, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 1060 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 5.300 lm 48.0 W 24 V DC 4000 K IP 20	261.05	234.94
560-290	833.76.365	Loox 5 3050, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 1080 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 5.400 lm 48.0 W 24 V DC 5000 K IP 20	261.05	234.94
560-291	833.76.370	Loox 5 3051, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1430 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 7.150 lm 72.0 W 24 V DC 2700 K IP 20	301.19	271.07
560-292	833.76.371	Loox 5 3051, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1520 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 7.600 lm 72.0 W 24 V DC 3000 K IP 20	301.19	271.07
560-293	833.76.372	Loox 5 3051, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1605 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 8.025 lm 72.0 W 24 V DC 4000 K IP 20	301.19	271.07
560-294	833.76.373	Loox 5 3051, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1650 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 8.250 lm 72.0 W 24 V DC 5000 K IP 20	301.19	271.07

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-295	833.76.378	Loox 5 3052, LED stripe self-adhesive cut length 50 mm, 19,2 W/m 1850 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 9.250 lm 96.0 W 24 V DC 2700 K IP 20	345.65	311.08
560-296	833.76.379	Loox 5 3052, LED stripe self-adhesive cut length 50 mm, 19,2 W/m 2015 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 10.075 lm 96.0 W 24 V DC 3000 K IP 20	345.65	311.08
560-297	833.76.380	Loox 5 3052, LED stripe self-adhesive cut length 50 mm, 19,2 W/m 2050 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 10.250 lm 96.0 W 24 V DC 4000 K IP 20	345.65	311.08
560-298	833.76.381	Loox 5 3052, LED stripe self-adhesive cut length 50 mm, 19,2 W/m 2100 lm/m, 140 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 10.500 lm 96.0 W 24 V DC 5000 K IP 20	345.65	311.08
560-299	833.76.332	Loox 5 3044, LED stripe self-adhesive cut length 50 mm, 4,8 W/m 425 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 2.125 lm 24.0 W 24 V DC TW 2700-5000 K IP 20	202.24	182.02
560-300	833.76.350	Loox 5 3047, LED stripe self-adhesive cut length 50 mm, 9,6 W/m 825 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 4.125 lm 48.0 W 24 V DC TW 2700-5000 K IP 20	262.49	236.24
560-301	833.76.360	Loox 5 3049, LED stripe self-adhesive cut length 50 mm, 14,4 W/m 1230 lm/m, 120 LEDs/m delivery length 5 m plastic, white CRI 90, energy efficiency class F 6.150 lm 72.0 W 24 V DC TW 2700-5000 K IP 20	302.63	272.37

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-308	850.00.043	Loox 5 Connect Mesh, distributor 6-way, with switching function & BT, maximum load 90 W output 6 x socket Loox 5, output 1 x socket box-to-box plastic, black 24 V DC, output 24 V DC, IP 20	107.34	96.61
560-309	850.00.040	Loox 5 Connect Mesh, remote control for distributor Connect Mesh, with Bluetooth® plastic, black / white IP 20	95.59	86.03
560-313	833.95.723	Loox 5 Profil 1103, recessed profile for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, black, anodised	47.35	42.61
560-315	833.95.722	Loox 5 Profil 1103, recessed profile for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, silver, anodised	45.91	41.32
560-316	833.95.767	Loox 5 Profil 1103, end cap box with 10 pcs plastic, black	6.90	6.21
560-317	833.95.766	Loox 5 Profil 1103, end cap box with 10 pcs plastic, silver	6.90	6.21
560-318	833.95.735	Loox 5 Profil 2102, profile for surface mounting for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, black, anodised	47.35	42.61
560-319	833.95.734	Loox 5 Profil 2102, profile for surface mounting for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, silver, anodised	45.91	41.32
560-320	833.95.763	Loox 5 Profil 2102, profile for surface mounting for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, silver, anodised	50.22	45.19
560-321	833.95.778	Loox 5 Profil 2102, end cap box with 10 pcs plastic, black	6.90	6.21
560-322	833.95.777	Loox 5 Profil 2102, end cap box with 10 pcs plastic, silver	6.90	6.21
560-323	833.95.779	Loox 5 Profil 2102, end cap box with 10 pcs plastic, stainless steel coloured	6.90	6.21
560-324	833.95.737	Loox 5 Profil 2103, profile for surface mounting for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, black, anodised	54.51	49.06

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-325	833.95.736	Loox 5 Profil 2103, profile for surface mounting for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, silver, anodised	50.22	45.19
560-326	833.95.764	Loox 5 Profil 2103, profile for surface mounting for LED stripes inner width 11 mm delivery length 3 m, with diffusor cover white opal, light transmission 70-80 % aluminium, stainless steel coloured, anodised	58.82	52.94
560-327	833.95.781	Loox 5 Profil 2103, end cap box with 10 pcs plastic, black	6.90	6.21
560-328	833.95.780	Loox 5 Profil 2103, end cap box with 10 pcs plastic, silver	6.90	6.21
560-329	833.95.782	Loox 5 Profil 2103, end cap box with 10 pcs plastic, stainless steel coloured	6.90	6.21
560-330	833.95.761	Loox 5 Profil 2103, mounting clip for concealed fixing box with 10 pcs stainless steel	6.90	6.21
560-331	833.75.743	Loox 5 for LED stripe monochrome 8 mm, version for 24 V DC, maximum load 5 A black IP 20	5.75	5.17
560-332	833.75.707	Loox 5 for LED stripe monochrome 8 mm, version for 24 V DC, maximum load 5 A black IP 20	7.19	6.47
560-333	833.75.706	Loox 5 for LED stripe monochrome 8 mm, version for 24 V DC, maximum load 5 A black IP 20	8.64	7.78
560-334	833.75.708	Loox 5 for LED stripe TW 8 mm, version for 24 V DC, maximum load 3,5 A black IP 20	10.06	9.05
560-336	833.77.830	Loox 5, adaptor tunable white for distributor Connect Mesh, without switching function, maximum load 90 W output 6 x socket Loox 5 TW plastic, black 24 V DC, output 24 V DC, IP 20	13.42	12.08
560-479	833.95.718	Loox 5, extension lead 24 V DC black	5.75	5.17
560-480	833.95.719	Loox 5, extension lead 24 V DC black	5.75	5.17

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-487	833.67.232	Q FOUR TT TRACK 40°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 40° beam angle, rotatable and tiltable black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	561.44	505.30
560-488	833.67.233	Q FOUR TT TRACK 40°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 40° beam angle, rotatable and tiltable black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	561.44	505.30
560-489	833.67.234	Q FOUR TT TRACK 40°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 40° beam angle, rotatable and tiltable black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	561.44	505.30
560-490	833.67.235	Q FOUR TT TRACK 40°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 40° beam angle, rotatable and tiltable white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	561.44	505.30
560-491	833.67.236	Q FOUR TT TRACK 40°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 40° beam angle, rotatable and tiltable white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	561.44	505.30
560-492	833.67.237	Q FOUR TT TRACK 40°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 40° beam angle, rotatable and tiltable white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	561.44	505.30
560-493	833.67.238	Q FOUR TT TRACK 80°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 80° beam angle, rotatable and tiltable black, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	561.44	505.30

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-494	833.67.239	Q FOUR TT TRACK 80°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 80° beam angle, rotatable and tiltable black, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	561.44	505.30
560-495	833.67.240	Q FOUR TT TRACK 80°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 80° beam angle, rotatable and tiltable black, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	561.44	505.30
560-496	833.67.241	Q FOUR TT TRACK 80°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 80° beam angle, rotatable and tiltable white, matt CRI 90 820 lm, 16,4 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	561.44	505.30
560-497	833.67.242	Q FOUR TT TRACK 80°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 80° beam angle, rotatable and tiltable white, matt CRI 90 900 lm, 16,4 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	561.44	505.30
560-498	833.67.243	Q FOUR TT TRACK 80°, track spotlight compatible with Nordic Global, LTS dimmable, DALI, for 3-phase track DALI 80° beam angle, rotatable and tiltable white, matt CRI 90 960 lm, 16,4 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	561.44	505.30
560-499	833.67.244	Q FOUR TT TRACK 40°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 40° beam angle, rotatable and tiltable black, matt CRI 90 820 lm, 16,0 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	475.53	427.98
560-500	833.67.245	Q FOUR TT TRACK 40°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 40° beam angle, rotatable and tiltable black, matt CRI 90 900 lm, 16,0 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	475.53	427.98

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-501	833.67.246	Q FOUR TT TRACK 40°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 40° beam angle, rotatable and tiltable black, matt CRI 90 960 lm, 16,0 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	475.53	427.98
560-502	833.67.247	Q FOUR TT TRACK 40°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 40° beam angle, rotatable and tiltable white, matt CRI 90 820 lm, 16,0 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	475.53	427.98
560-503	833.67.248	Q FOUR TT TRACK 40°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 40° beam angle, rotatable and tiltable white, matt CRI 90 900 lm, 16,0 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	475.53	427.98
560-504	833.67.249	Q FOUR TT TRACK 40°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 40° beam angle, rotatable and tiltable white, matt CRI 90 960 lm, 16,0 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	475.53	427.98
560-505	833.67.250	Q FOUR TT TRACK 80°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 80° beam angle, rotatable and tiltable black, matt CRI 90 820 lm, 16,0 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	475.53	427.98
560-506	833.67.251	Q FOUR TT TRACK 80°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 80° beam angle, rotatable and tiltable black, matt CRI 90 900 lm, 16,0 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	475.53	427.98
560-507	833.67.252	Q FOUR TT TRACK 80°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 80° beam angle, rotatable and tiltable black, matt CRI 90 820 lm, 16,0 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	475.53	427.98

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-508	833.67.253	Q FOUR TT TRACK 80°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 80° beam angle, rotatable and tiltable white, matt CRI 90 820 lm, 16,0 W, 230 V AC, 50 Hz, 2700 K, IP 20 NP	475.53	427.98
560-509	833.67.254	Q FOUR TT TRACK 80°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 80° beam angle, rotatable and tiltable white, matt CRI 90 900 lm, 16,0 W, 230 V AC, 50 Hz, 3000 K, IP 20 NP	475.53	427.98
560-510	833.67.255	Q FOUR TT TRACK 80°, track spotlight compatible with Eutrac, Nordic Global, SLV switchable, for 3-phase track 80° beam angle, rotatable and tiltable white, matt CRI 90 960 lm, 16,0 W, 230 V AC, 50 Hz, 4000 K, IP 20 NP	475.53	427.98
560-817	833.67.584	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, black ink CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
560-818	833.67.585	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, black ink CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
560-819	833.67.586	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, black ink CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
560-820	833.67.597	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, black ink CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-823	833.67.596	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, black ink CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
560-824	833.67.599	LIGHTING PAD Q 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, black ink CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
560-825	833.67.590	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, black ink CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
560-826	833.67.591	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, black ink CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
560-827	833.67.593	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, black ink CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
560-829	833.67.604	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, black ink CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-830	833.67.602	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, black ink CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76
560-831	833.67.603	LIGHTING PAD Q 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, black ink CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
560-832	833.67.587	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, black ink CRI 90 4.200 lm, 63,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2084.83	1876.35
560-833	833.67.588	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, black ink CRI 90 4.620 lm, 63,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2084.83	1876.35
560-834	833.67.589	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B double-sided without suspension kit fleece, black ink CRI 90 5.010 lm, 63,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2084.83	1876.35
560-835	833.67.598	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, black ink CRI 90 1.510 lm, 27,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1655.28	1489.75

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-836	833.67.600	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, black ink CRI 90 1.660 lm, 27,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1655.28	1489.75
560-837	833.67.601	LIGHTING PAD R 600, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class B single-sided without suspension kit fleece, black ink CRI 90 1.770 lm, 27,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1655.28	1489.75
560-838	833.67.592	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, black ink CRI 90 4.900 lm, 74,4 W, 230 V AC, 50 Hz, 2700 K, IP 20	2371.60	2134.44
560-839	833.67.594	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, black ink CRI 90 5.460 lm, 74,4 W, 230 V AC, 50 Hz, 3000 K, IP 20	2371.60	2134.44
560-840	833.67.595	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A double-sided without suspension kit fleece, black ink CRI 90 5.900 lm, 74,4 W, 230 V AC, 50 Hz, 4000 K, IP 20	2371.60	2134.44
560-841	833.67.606	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, black ink CRI 90 2.210 lm, 38,2 W, 230 V AC, 50 Hz, 2700 K, IP 20	1940.84	1746.76

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-842	833.67.605	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, black ink CRI 90 2.500 lm, 38,2 W, 230 V AC, 50 Hz, 3000 K, IP 20	1940.84	1746.76
560-843	833.67.607	LIGHTING PAD R 900, acoustic luminaire suspended mounting dimmable, DALI/switchDIM, capable for video conferencing, absorber class A single-sided without suspension kit fleece, black ink CRI 90 2.660 lm, 38,2 W, 230 V AC, 50 Hz, 4000 K, IP 20	1940.84	1746.76
561-153		AIR MAXX 250 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, frosted silver, matt, anodised CRI 90 2.300 lm, 33.0 W, 230 V AC, 50/60 Hz, 2700 K, IP 20	654.61	589.15
561-154		AIR MAXX 250 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, frosted silver, matt, anodised CRI 90 2.300 lm, 33.0 W, 230 V AC, 50/60 Hz, 3000 K, IP 20	654.61	589.15
561-155		AIR MAXX 250 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, brilliant, chrome plated CRI 90 2.300 lm, 33.0 W, 230 V AC, 50/60 Hz, 2700 K, IP 20	734.47	661.02
561-156		AIR MAXX 250 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, brilliant, chrome plated CRI 90 2.300 lm, 33.0 W, 230 V AC, 50/60 Hz, 3000 K, IP 20	734.47	661.02
561-157		AIR MAXX 130 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, frosted silver, matt, anodised CRI 90 1.200 lm, 18.0 W, 230 V AC, 50/60 Hz, 2700 K, IP 20	510.62	459.56
561-158		AIR MAXX 130 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, frosted silver, matt, anodised CRI 90 1.200 lm, 18.0 W, 230 V AC, 50/60 Hz, 3000 K, IP 20	510.62	459.56

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
561-159		AIR MAXX 130 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, brilliant, chrome plated CRI 90 1.200 lm, 18.0 W, 230 V AC, 50/60 Hz, 2700 K, IP 20	575.96	518.36
561-160		AIR MAXX 130 SUPER POWER, wall luminaire with wall mounting set dimmable, 1-10 V, version for 230 V AC double-sided aluminium, brilliant, chrome plated CRI 90 1.200 lm, 18.0 W, 230 V AC, 50/60 Hz, 3000 K, IP 20	575.96	518.36
562-191		ROXXANE LEGGERA 52 SET, desk luminaire with gesture control, with lithium-ion battery, cableless with USB charging cable, with Magnetic Dock aluminium, ruby red, matt, powder-coated CRI 90 800 lm, 2700 K, IP 20 NP	831.74	748.57
560-302	833.95.008	Loox 5, power supply constant voltage output 1 x socket Loox 5 plastic, black 230 V AC, 50-60 Hz, output 24 V DC, 20 W, IP 20	38.93	35.03
560-303	833.95.010	Loox 5, power supply constant voltage output 1 x socket Loox 5 plastic, black 230 V AC, 50-60 Hz, output 24 V DC, 40 W, IP 20	40.14	36.12
560-304	833.95.011	Loox 5, power supply constant voltage output 1 x socket Loox 5 plastic, black 230 V AC, 50-60 Hz, output 24 V DC, 90 W, IP 20	143.55	129.20
560-305	833.95.012	Loox 5, power supply constant voltage output 1 x socket Loox 5 plastic, black 230 V AC, 50-60 Hz, output 24 V DC, 240 W, IP 20	297.85	268.07
560-306	833.89.002	Loox 5, mains cable power supply with EU power plug black	7.20	6.48
560-307	833.89.258	Loox 5, mains cable power supply with EU power plug for 240 W power supply black	11.50	10.35
560-310	850.00.041	Loox 5 Connect Mesh, wall mounted push button for distributor Connect Mesh, with Bluetooth® plastic, black / white IP 20	84.70	76.23
560-311	850.00.046	Loox 5 Connect Mesh, 230 V interface for distributor Connect Mesh, with Bluetooth® IP 20	91.80	82.62
560-312	850.00.047	Loox 5 Connect Mesh, interface for distributor Connect Mesh, with Bluetooth®, battery operated with 4 switching inputs black IP 20	57.39	51.65

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-335	833.77.832	Loox 5, distributor 6-way, without switching function, maximum load 90 W output 6 x socket Loox 5, output 1 x socket box-to-box plastic, black 24 V DC, output 24 V DC, IP 20	8.07	7.26
560-475	833.67.256	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, gesture control/Bluetooth®, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Santos Rosewood CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	4086.55	3677.89
560-476	833.67.257	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Black Cherry CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3966.56	3569.91
560-478	833.95.717	Loox 5, extension lead 24 V DC black, length 2 m, 5A, 24 V DC, 18 AWG	8.64	7.78
560-571	833.67.258	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Santos Rosewood CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3365.63	3029.06
560-572	833.67.259	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Black Cherry CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3243.61	2919.25

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-573	833.67.260	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Classic Oak CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3123.63	2811.26
560-574	833.67.261	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Classic Oak CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	2401.69	2161.52
560-664	833.67.289	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Santos Rosewood CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	4086.55	3677.89
560-665	833.67.290	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Santos Rosewood CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3365.63	3029.06
560-865	833.67.490	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Classic Oak CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3123.63	2811.26

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-866	833.67.491	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Classic Oak CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3123.63	2811.26
560-867	833.67.492	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Black Cherry CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3966.56	3569.91
560-868	833.67.493	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Black Cherry CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3966.56	3569.91
560-869	833.67.494	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Santos Rosewood CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	4086.55	3677.89
560-871	833.67.495	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Classic Oak CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	2401.69	2161.52

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
560-872	833.67.496	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Classic Oak CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	2401.69	2161.52
560-873	833.67.497	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Black Cherry CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3243.61	2919.25
560-875	833.67.498	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Black Cherry CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3243.61	2919.25
560-876	833.67.499	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Santos Rosewood CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3365.63	3029.06
561-302	833.67.610	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Ebony Ash CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3966.56	3569.91

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
561-324	833.67.613	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Ebony Ash CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3966.56	3569.91
561-382	833.67.608	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, black ink, shaped wood Ebony Ash CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3243.61	2919.25
561-440	833.67.612	LIGHTING PAD LOUNGE R 600 VARIO, acoustic luminaire suspended mounting, variable pendant length, adjustable from 500 to 2000 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Ebony Ash CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3966.56	3569.91
561-444	833.67.609	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, grey dawn, shaped wood Ebony Ash CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3243.61	2919.25
561-446	833.67.611	LIGHTING PAD LOUNGE R 600, acoustic luminaire suspended mounting, fixed pendant length, max. suspension length 3500 mm Control via häfele connect, with gesture control /BLE, absorber class B double-sided, power supply by pendulum ropes with suspension kit, with canopy incl. converter fleece, white, shaped wood Ebony Ash CRI 90 3.500 lm, 60,0 W, 100-240 V AC, 50/60 Hz, TW 2700-4000 K, IP 20	3243.61	2919.25
561-944	850.00.024	Connect Mesh, wall switch direct mounting, self-adhesive control via Bluetooth® with double rocker, 4 programmable functions white	119.79	107.81

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-303	833.67.760	MODUL Q 16 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 300 lm, 3.5 W, 24 V DC, TW 2700-5000 K, IP 20	181.50	163.35
562-304	833.67.761	MODUL Q 36 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 675 lm, 7.5 W, 24 V DC, TW 2700-5000 K, IP 20	257.73	231.96
562-305	833.67.762	MODUL Q 49 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 920 lm, 9.5 W, 24 V DC, TW 2700-5000 K, IP 20	342.43	308.19
562-306	833.67.763	MODUL Q 64 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 1,200 lm, 12.5 W, 24 V DC, TW 2700-5000 K, IP 20	504.57	454.11
562-307	833.67.764	MODUL Q 100 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 1,880 lm, 18.0 W, 24 V DC, TW 2700-5000 K, IP 20	652.19	586.97
562-308	833.67.765	CUBIC 16 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 265 lm, 3.5 W, 24 V DC, TW 2700-5000 K, IP 20	181.50	163.35
562-309	833.67.766	CUBIC 36 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 605 lm, 7.5 W, 24 V DC, TW 2700-5000 K, IP 20	257.73	231.96
562-310	833.67.767	CUBIC 49 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 825 lm, 9.5 W, 24 V DC, TW 2700-5000 K, IP 20	342.43	308.19

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-311	833.67.768	CUBIC 64 Connect ON, ceiling luminaire direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector acrylic, satin-frosted CRI 90 1.075 lm, 12.5 W, 24 V DC, TW 2700-5000 K, IP 20	504.57	454.11
562-314	833.67.771	Q Four Connect ON 40°, ceiling spotlight direct mounting control via Häfele Connect 40° beam angle with mounting ring, with Loox5 24 V connector white, matt CRI 90 680 lm, 15.0 W, 24 V DC, TW 2700-5000 K, IP 20	284.35	255.92
562-315	833.67.772	Q Four Connect ON 80°, ceiling spotlight direct mounting control via Häfele Connect 80° beam angle with mounting ring, with Loox5 24 V connector white, matt CRI 90 900 lm, 15.0 W, 24 V DC, TW 2700-5000 K, IP 20	284.35	255.92
562-316	833.67.773	Q Four Connect ON 40°, ceiling spotlight direct mounting control via Häfele Connect 40° beam angle with mounting ring, with Loox5 24 V connector black, matt CRI 90 680 lm, 15.0 W, 24 V DC, TW 2700-5000 K, IP 20	284.35	255.92
562-317	833.67.774	Q Four Connect ON 80°, ceiling spotlight direct mounting control via Connect Mesh 80° beam angle with mounting ring, with Loox5 24 V connector black, matt CRI 90 900 lm, 15.0 W, 24 V DC, TW 2700-5000 K, IP 20	284.35	255.92
562-337	833.67.779	accessory Connect, ceiling ring cavity mounting / HaloX-O, to drill and clamp	33.88	30.49
562-338	833.67.780	accessory Connect, ceiling ring cavity mounting TT, for drilling and clamping, only for TT versions, with protection against twisting by locking pin	58.08	52.27
562-359	833.75.769	Loox5 distributor, lenght 0.14 m, 5 A, 24 V DC, 18 AWG, 2-adrig, 2-core	6.05	5.45
562-536	850.00.952	Loox5 Connect Mesh furniture switch with push button for connect mesh, bluetooth technolgoy, IP20, not included in the scope of delivery: Lithium cell CR2032	71.39	64.25
562-538	833.77.839	Loox5 6-way distributor, max. load 120 W, IP 20, 24 V DC	10.29	9.26
562-552	833.75.768	Loox5 distributor Y-extension cable 24V, lenght 0.14 m, 5 A, 24 V DC, 18 AWG, 2- adrig, 2-core	6.05	5.45

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-553	833.67.902	Q Four Connect TT 40°, ceiling spotlight direct mounting control via Häfele Connect 40° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector white, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	393.25	353.93
562-558	833.67.900	Q Four Connect ON-XD 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle with mounting ring, with converter white, matt CRI 90 680 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	381.15	343.04
562-559	833.67.901	Q Four Connect ON-X 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle with mounting ring, with Loox5 24 V connector white, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	331.54	298.39
562-561	833.67.903	Q Four Connect TT-XD 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle, rotatable and tiltable with mounting ring, with converter white, matt CRI 90 680 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05
562-563	833.67.904	Q Four Connect TT-X 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector white, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	440.44	396.40
562-564	833.67.905	Q Four Connect TT Track 40°, track spotlight for 230 V AC rail system, compatible with Global, Stucchi, Eutrac, Erco control via Häfele Connect, with integrated converter 40° beam angle, rotatable and tiltable white, matt CRI 90 680 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-565	833.67.906	Q Four Connect IN 40°, recessed ceiling spot cavity mounting control via Häfele Connect 40° beam angle with recessed ceiling frame, with Loox5 24 V connector white, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	320.65	288.59
562-568	833.67.907	Q Four Connect ON-XD 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle with mounting ring, with converter white, matt CRI 90 900 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	381.15	343.04
562-569	833.67.908	Q Four Connect ON-X 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle with mounting ring, with Loox5 24 V connector white, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	331.54	298.39
562-570	833.67.909	Q Four Connect TT 80°, ceiling spotlight direct mounting control via Häfele Connect 80° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector white, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	393.25	353.93
562-571	833.67.910	Q Four Connect TT-XD 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle, rotatable and tiltable with mounting ring, with converter white, matt CRI 90 900 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05
562-572	833.67.911	Q Four Connect TT-X 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector white, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	440.44	396.40

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-573	833.67.912	Q Four Connect TT Track 80°, track spotlight for 230 V AC rail system, compatible with Global, Stucchi, Eutrac, Erco control via Häfele Connect, with integrated converter 80° beam angle, rotatable and tiltable white, matt CRI 90 900 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05
562-574	833.67.913	Q Four Connect IN 80°, recessed ceiling spot cavity mounting control via Häfele Connect 80° beam angle with recessed ceiling frame, with Loox5 24 V connector white, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	320.65	288.59
562-584	833.67.914	Q Four Connect ON-XD 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle with mounting ring, with converter black, matt CRI 90 680 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	381.15	343.04
562-585	833.67.915	Q Four Connect ON-X 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle with mounting ring, with Loox5 24 V connector black, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	331.54	298.39
562-586	833.67.916	Q Four Connect TT 40°, ceiling spotlight direct mounting control via Häfele Connect 40° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector black, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	393.25	353.93
562-587	833.67.917	Q Four Connect TT-XD 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle, rotatable and tiltable with mounting ring, with converter black, matt CRI 90 680 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-589	833.67.918	Q Four Connect TT-X 40°, surface-mounted ceiling spot direct mounting control via Häfele Connect 40° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector black, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	440.44	396.40
562-590	833.67.919	Q Four Connect TT Track 40°, track spotlight for 230 V AC rail system, compatible with Global, Stucchi, Eutrac, Erco control via Häfele Connect, with integrated converter 40° beam angle, rotatable and tiltable black, matt CRI 90 680 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05
562-591	833.67.920	Q Four Connect IN 40°, recessed ceiling spot cavity mounting control via Häfele Connect 40° beam angle with recessed ceiling frame, with Loox5 24 V connector black, matt CRI 90 680 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	320.65	288.59
562-594	833.67.921	Q Four Connect ON-XD 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle with mounting ring, with converter black, matt CRI 90 900 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	381.15	343.04
562-595	833.67.922	Q Four Connect ON-X 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle with mounting ring, with Loox5 24 V connector black, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	331.54	298.39
562-596	833.67.923	Q Four Connect TT 80°, ceiling spotlight direct mounting control via Häfele Connect 80° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector black, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	393.25	353.93

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-597	833.67.924	Q Four Connect TT-XD 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle, rotatable and tiltable with mounting ring, with converter black, matt CRI 90 900 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05
562-598	833.67.925	Q Four Connect TT-X 80°, surface-mounted ceiling spot direct mounting control via Häfele Connect 80° beam angle, rotatable and tiltable with mounting ring, with Loox5 24 V connector black, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	440.44	396.40
562-599	833.67.926	Q Four Connect TT Track 80°, track spotlight for 230 V AC rail system, compatible with Global, Stucchi, Eutrac, Erco control via Häfele Connect, with integrated converter 80° beam angle, rotatable and tiltable black, matt CRI 90 900 lm, 17,5 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	490.05	441.05
562-600	833.67.927	Q Four Connect IN 80°, recessed ceiling spot cavity mounting control via Häfele Connect 80° beam angle with recessed ceiling frame, with Loox5 24 V connector black, matt CRI 90 900 lm, 15,0 W, 24 V DC, TW 2700-5000 K, IP 20	320.65	288.59
562-610	833.67.928	MODUL Q 36 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 675 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	365.42	328.88
562-611	833.67.929	MODUL Q 36 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 675 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	365.42	328.88

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-612	833.67.930	MODUL Q 36 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector white, matt CRI 90 675 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	315.81	284.23
562-613	833.67.931	MODUL Q 36 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 675 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	315.81	284.23
562-620	833.67.932	MODUL Q 36 Connect TT, ceiling luminaire direct mounting control via Häfele Connect rotatable and tiltable with mounting ring, with Loox5 24 V connector white, matt CRI 90 675 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	377.52	339.77
562-621	833.67.933	MODUL Q 36 Connect TT, ceiling luminaire direct mounting control via Häfele Connect rotatable and tiltable with mounting ring, with Loox5 24 V connector black, matt CRI 90 675 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	377.52	339.77
562-622	833.67.934	MODUL Q 36 Connect TT-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter rotatable and tiltable with mounting ring white, matt CRI 90 675 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	474.32	426.89
562-623	833.67.935	MODUL Q 36 Connect TT-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter rotatable and tiltable with mounting ring black, matt CRI 90 675 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	474.32	426.89

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-624	833.67.936	MODUL Q 36 Connect TT-X, surface-mounted ceiling light direct mounting control via Häfele Connect rotatable and tiltable with mounting ring, with Loox5 24 V connector white, matt CRI 90 675 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	424.71	382.24
562-625	833.67.937	MODUL Q 36 Connect TT-X, surface-mounted ceiling light direct mounting control via Häfele Connect rotatable and tiltable with mounting ring, with Loox5 24 V connector black, matt CRI 90 675 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	424.71	382.24
562-626	833.67.938	MODUL Q 36 Connect TT Track, track spotlight for 230 V AC rail system, compatible with Global, Stucchi, Eutrac, Erco control via Häfele Connect, with integrated converter rotatable and tiltable white, matt CRI 90 675 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	474.32	426.89
562-627	833.67.939	MODUL Q 36 Connect TT Track, track spotlight for 230 V AC rail system, compatible with Global, Stucchi, Eutrac, Erco control via Häfele Connect, with integrated converter rotatable and tiltable black, matt CRI 90 675 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	474.32	426.89
562-629	833.67.940	MODUL Q 49 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 920 lm, 11,0 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	439.23	395.31
562-630	833.67.941	MODUL Q 49 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 920 lm, 11,0 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	439.23	395.31

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-631	833.67.942	MODUL Q 49 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector white, matt CRI 90 920 lm, 9,5 W, 24 V DC, TW 2700-5000 K, IP 20	389.62	350.66
562-632	833.67.943	MODUL Q 49 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 920 lm, 9,5 W, 24 V DC, TW 2700-5000 K, IP 20	389.62	350.66
562-634	833.67.944	MODUL Q 64 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 1.200 lm, 14,4 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	601.37	541.23
562-635	833.67.945	MODUL Q 64 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 1.200 lm, 14,4 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	601.37	541.23
562-636	833.67.946	MODUL Q 64 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector white, matt CRI 90 1.200 lm, 12,5 W, 24 V DC, TW 2700-5000 K, IP 20	551.76	496.58
562-637	833.67.947	MODUL Q 64 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 1.200 lm, 12,5 W, 24 V DC, TW 2700-5000 K, IP 20	551.76	496.58

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-641	833.67.948	MODUL Q 100 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 1.880 lm, 21,0 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	748.99	674.09
562-642	833.67.949	MODUL Q 100 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 1.880 lm, 21,0 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	748.99	674.09
562-643	833.67.980	MODUL Q 100 Connect ON-X, surface-mounted ceiling light direct mounting control via Connect Mesh with mounting ring, with Loox5 24 V connector white, matt CRI 90 1.880 lm, 18,0 W, 24 V DC, TW 2700-5000 K, IP 20	699.38	629.44
562-644	833.67.981	MODUL Q 100 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 1.880 lm, 18,0 W, 24 V DC, TW 2700-5000 K, IP 20	699.38	629.44
562-647	833.67.982	CUBIC 36 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 605 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	354.53	319.08
562-648	833.67.983	CUBIC 36 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 605 lm, 8,7 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	354.53	319.08

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-649	833.67.984	CUBIC 36 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector white, matt CRI 90 605 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	304.92	274.43
562-650	833.67.985	CUBIC 36 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 605 lm, 7,5 W, 24 V DC, TW 2700-5000 K, IP 20	304.92	274.43
562-652	833.67.986	CUBIC 49 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 825 lm, 11,0 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	439.23	395.31
562-653	833.67.987	CUBIC 49 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 825 lm, 11,0 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	439.23	395.31
562-654	833.67.988	CUBIC 49 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector white, matt CRI 90 825 lm, 9,5 W, 24 V DC, TW 2700-5000 K, IP 20	389.62	350.66
562-655	833.67.989	CUBIC 49 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 825 lm, 9,5 W, 24 V DC, TW 2700-5000 K, IP 20	389.62	350.66
562-657	833.67.990	CUBIC 64 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring white, matt CRI 90 1.075 lm, 14,4 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	601.37	541.23

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
562-658	833.67.991	CUBIC 64 Connect ON-XD, surface-mounted ceiling light direct mounting control via Häfele Connect, with integrated converter with mounting ring black, matt CRI 90 1.075 lm, 14,4 W, 230 V AC, 50 Hz, TW 2700-5000 K, IP 20	601.37	541.23
562-659	833.67.992	CUBIC 64 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector white, matt CRI 90 1.075 lm, 12,5 W, 24 V DC, TW 2700-5000 K, IP 20	551.76	496.58
562-660	833.67.993	CUBIC 64 Connect ON-X, surface-mounted ceiling light direct mounting control via Häfele Connect with mounting ring, with Loox5 24 V connector black, matt CRI 90 1.075 lm, 12,5 W, 24 V DC, TW 2700-5000 K, IP 20	551.76	496.58
562-661	833.67.994	ZEN Connect ON, wall luminaire, near-ground for wall mounting, "ON" Module for screwing onto flush-mounted box / mounting box control via Häfele Connect with Loox5 24 V connector white, matt CRI 90 100 lm, 1,7 W, 24 V DC, TW 2700-5000 K, IP 20	169.40	152.46
562-662	833.67.995	ZEN Connect ON, wall luminaire, near-ground for wall mounting, "ON" Module for screwing onto flush-mounted box / mounting box control via Häfele Connect with Loox5 24 V connector black, matt CRI 90 100 lm, 1,7 W, 24 V DC, TW 2700-5000 K, IP 20	169.40	152.46
562-663	833.67.996	ZEN Connect IN, wall luminaire, near-ground cavity mounting, with "IN" kit for cavity installation Control via Häfele Connect control via Häfele Connect with cavity bracket, with Loox5 24 V connector white, matt CRI 90 100 lm, 1,7 W, 24 V DC, TW 2700-5000 K, IP 20	181.50	163.35
562-664	833.67.997	ZEN Connect IN, wall luminaire, near-ground cavity mounting control via Häfele Connect with cavity bracket, with Loox5 24 V connector black, matt CRI 90 100 lm, 1,7 W, 24 V DC, TW 2700-5000 K, IP 20	181.50	163.35
562-829	002.99.034	Button cell, Lithium, 3V, CR2430	4.48	4.03
562-830	002.99.032	Button cell, Lithium, 3V, CR2032	2.06	1.85

Nimbus prekės kodas	Häfele prekės kodas	Aprašas (EN)	Kaina su PVM, Eur	Kaina su nuolaida su PVM, Eur
------------------------	------------------------	--------------	-------------------	----------------------------------

Upon publication of this price list all our previous price information loses its validity.

Converters are not included, if not mentioned otherwise. Subject to alterations in design, price and technical details. All technical details are subject to a tolerance of 10 % due to differences in construction and/or the components used.

We accept no liability for any printing errors on the pricelist. Data files for light calculation (Eulumdat) as well as mounting instructions with pictures can be found in the download area of our website at www.nimbus-lighting.com.

The General Terms of Business of the Nimbus Group are applicable and can be viewed at www.nimbus-group.com.

Please note that our products correspond to European technical standards and CE certification.

All technical details are based on the 2700 K, 3000 K and 4000 K versions of our luminaires.

Nimbus Group GmbH, www.nimbus-group.com

Brasa UAB, www.brasa.lt